

100W AC-DC ATX Power



210x 85x 46 mm

- Universal AC input / Full range
- No load power consumption < 1W @240VAC
- 3 pole AC inlet IEC320-C14
- Built-in active PFC function, PF>0.95
- Class I power (with earth pin)
- Protections: Short circuit / Overload / Over voltage / Over temp.
- Power on LED indicator
- Fully enclosed plastic case
- 2 years warranty

Setup, rise, hold up time 3000ms, 80ms, 40ms at full load and 230VAC
 Overload protection 140%~200% load, shut off
 Over voltage protection 110%~130% rated output voltage (CH1,2,3)
 Withstand voltage I/P-O/P:3kVAC
 Working temperature 0~+40°C@100%, 50°C@80% load
 Safety standards IEC60950-1 CB approved by TUV
 EMC standards EN55022 class B, EN61000-3-2,3, EN61204-3, EN61000-4-2,3,4,5,6,8,11, ENV50204
 Length of output cable 65cm of UL rated, 18AWGx20C
 Standard DC plug Molex 39-01-2200 or equivalent

Order No.	Output	Tol.	R&N	Effi.	Max.
ATX-100	3.3V, 0~6.0A	±5%	100mV	80%	100W
	5V, 0~8.0A	±5%	100mV		(cont.)
	12V, 1~7.0A	±5%	120mV		125W
	-12V, 0~0.5A	±10%	120mV		(7 min.)
	5VSB, 0~2.0A	±5%	100mV		150W
					(3 min.)