



Test Report: GST280A15-C6P

280W AC-DC High Reliability Industrial Adaptor

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE(Max)	V1: 120mVp-p	I/P:230VAC O/P:FULL LOAD Ta:25°C	V1: 11.6mVp-p	P
2	OUTPUT VOLTAGE(Max) TOLERANCE	V1: -5%~ 5%	I/P: 100VAC /264VAC O/P:FULL/ MIN. LOAD Ta:25°C	V1: -1.841%~ 2.003%	P
3	LINE REGULATION (Max)	V1: -1%~ 1%	I/P: 100VAC~ 264VAC O/P:FULL LOAD Ta:25°C	V1: 0 %~ 0.04 %	P
4	LOAD REGULATION(Max)	V1: -5%~ 5%	I/P: 230VAC O/P:FULL -MIN LOAD Ta:25°C	V1: -1.841%~ 2.003%	P
5	SET UP TIME(Max)	230VAC/2000ms 115VAC/2000ms	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 1230.566ms 115VAC/ 1132.828ms	P
6	RISE TIME (Max)	230VAC/20ms 115VAC/20ms	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 9.148ms 115VAC/ 9.498ms	P
7	HOLD UP TIME(Typ)	230VAC/16ms 115VAC/16ms	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 23.932ms 115VAC/ 23.750ms	P
8	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230VAC O/P:FULL LOAD Ta:25°C	< ±5%	P
9	DYNAMIC LOAD	V1: 1500mVp-p	I/P: 230VAC O/P(1)FULL /Min LOAD 90%DUTY / 1KHZ (2) (1)FULL /Min LOAD 90%DUTY / 3KHZ (3)FULL /Min LOAD 90%DUTY / 5KHZ (4)FULL /Min LOAD 50%DUTY / 120HZ Ta:25°C	1020mVp-p 1000mVp-p 1020mVp-p 988mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	100VAC~264VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	54.987 V~264V	P
			I/P: (1)LOW-LINE-3V=87 V HIGH-LINE+15%=300 V O/P:FULL/MIN LOAD ON: 30 Sec OFF: 30 Sec 10MIN (2)230Vac ON: 0.5 Sec OFF: 0.5 Sec 20MIN (3)230Vac ON:3Sec OFF:3Sec 12HOURS (POWER ON/OFF NO DAMAGE)	TEST:OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P:100 VAC ~264 VAC O/P:FULL-MIN LOAD Ta:25°C	TEST: OK	P
3	POWER FACTOR(TYP)	0.95/ 230VAC 0.98/115VAC	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	PF=0.957/230VAC PF=0.995/115VAC	P
4	EFFICIENCY(TYP)	90%	I/P:230 VAC O/P:FULL LOAD Ta:25°C	90.85%	P
5	INPUT CURRENT (Typ)	230V/ 1.5A 115V/ 3A	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I =1.26A/ 230VAC I =2.51A/ 115VAC	P
6	INRUSH CURRENT(Typ)	230VAC/120A 115VAC/60A COLD START	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 113 A/ 230VAC I = 57 A/ 115VAC	P
7	LEAKAGE CURRENT	< 1.5 mA / 240 VAC	I/P : 240 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.780 mA N-FG : 0.780 mA	P
8	NO LOAD CONSUMPTION	< 0.5 W	I/P : 115VAC I/P : 230VAC O/P : NO LOAD Ta : 25°C	< 0.33 W < 0.43 W	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105%~ 135%	I/P: 230VAC I/P: 115VAC O/P: TESTING Ta:25°C	118.52%/ 230VAC 118.12%/115VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH:15.75V~20.25V	I/P: 230VAC I/P: 115VAC O/P: MIN LOAD Ta:25°C	18.5V/ 230VAC 18.5V/115VAC Shut down Re- power ON	P
3	OVER TEMPERATURE PROTECTION	NO DAMAGE	I/P: 230 VAC O/P: FULL LOAD	O.T.P. Active Shunt down Re-power ON	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264VAC O/P: FULL LOAD Ta:25°C	NO DAMAGE (1) Hiccup Mode	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	PWM Transistor (D to S) or (C to E) Peak Voltage	Q5 Rated : 16A/ 600V	I/P: High-Line +3V =267V AC ON/OFF VDS: O/P: (1) Full Load (2) Output Short (3) Full Load Continue Ta:25°C	(1) 484V (2) 510V (3) 452V	P
2	Diode Peak Voltage	Q101 Rated 183A/75V	I/P: High-Line +3V =267V AC ON/OFF VDS: O/P: (1) Full Load (2) Output Short (3) Full Load Continue Ta:25°C	Q101: (1) 60.6V (2) 18.3V (3) 40.6V	P
3	Input Capacitor Voltage	C5 Rated: : 220 μ / 450V 105°C	I/P: High-Line +3V =267 V O/P: (1) Full Load input on/off (2) Min load input on /Off (3) Full Load /Min load Change Ta:25°C	(1) 432V (2) 436V (3) 436V	P
4	Control IC Voltage Test	PWM IC U900 Rated : 16V 8.85V(MIN.)	I/P: High-Line +3V =267 V AC ON/OFF O/P: (1) FULL LOAD (2) Output Short (3) O.L.P (4) NO LOAD VR MIN LOW LINE Ta:25°C	(1) 15.6V (2) 15.5V (3) 15.5V (4) 15.2V	P
6	P.F.C Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated : 20 A/ 600V	I/P: High-Line +3V =267V AC ON/OFF VDS: O/P: (1) Full Load (2) Output Short (3) Full Load Continue Ta:25°C	(1) 506V (2) 506V (3) 508V	P

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 3KVAC/min I/P-FG:2KVAXI/min	I/P-O/P: 3.6 KVAC/min I/P-FG:2.4KVAXI/min Ta:25°C	I/P-O/P:3.101mA I/P-FG:2.52mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25°C	I/P-O/P: 9999MΩ NO DAMAGE	P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N : 1KV L,N-PE : 2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																
1	TEMPERATURE RISE TEST	MODEL : GST280A15-C6P 1. ROOM AMBIENT BURN-IN : 1HRS I/P : 230VAC O/P : FULL LOAD Ta=17.8 °C 2. HIGH AMBIENT BURN-IN : 1HRS I/P : 230VAC O/P : FULL LOAD Ta=38.4 °C	<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 17.8 °C</th> <th>HIGH AMBIENT Ta= 38.4 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF2</td><td>60.0°C</td><td>79.1°C</td></tr> <tr><td>2</td><td>Q2</td><td>66.1°C</td><td>85.1°C</td></tr> <tr><td>3</td><td>Q1</td><td>64.3°C</td><td>83.3°C</td></tr> <tr><td>4</td><td>BD1</td><td>63.5°C</td><td>82.2°C</td></tr> <tr><td>5</td><td>D2</td><td>66.3°C</td><td>85.2°C</td></tr> <tr><td>6</td><td>Q5</td><td>66.0°C</td><td>85.3°C</td></tr> <tr><td>7</td><td>Q6</td><td>65.7°C</td><td>85.0°C</td></tr> <tr><td>8</td><td>L1</td><td>66.1°C</td><td>84.9°C</td></tr> <tr><td>9</td><td>C5</td><td>67.2°C</td><td>86.2°C</td></tr> <tr><td>10</td><td>RTH2</td><td>62.4°C</td><td>81.4°C</td></tr> <tr><td>11</td><td>TI Coil</td><td>73.6°C</td><td>93.3°C</td></tr> <tr><td>12</td><td>Q102</td><td>73.2°C</td><td>93.0°C</td></tr> <tr><td>13</td><td>C101</td><td>74.2°C</td><td>94.4°C</td></tr> <tr><td>14</td><td>LF101</td><td>78.5°C</td><td>99.5°C</td></tr> <tr><td>15</td><td>U1</td><td>62.8°C</td><td>81.8°C</td></tr> <tr><td>16</td><td>U900</td><td>65.6°C</td><td>84.9°C</td></tr> <tr><td>17</td><td>U201</td><td>69.1°C</td><td>88.9°C</td></tr> <tr><td>18</td><td>T1core</td><td>80.5°C</td><td>101.9°C</td></tr> <tr><td>19</td><td>CASE</td><td>49.0°C</td><td>67.6°C</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 17.8 °C	HIGH AMBIENT Ta= 38.4 °C	1	LF2	60.0°C	79.1°C	2	Q2	66.1°C	85.1°C	3	Q1	64.3°C	83.3°C	4	BD1	63.5°C	82.2°C	5	D2	66.3°C	85.2°C	6	Q5	66.0°C	85.3°C	7	Q6	65.7°C	85.0°C	8	L1	66.1°C	84.9°C	9	C5	67.2°C	86.2°C	10	RTH2	62.4°C	81.4°C	11	TI Coil	73.6°C	93.3°C	12	Q102	73.2°C	93.0°C	13	C101	74.2°C	94.4°C	14	LF101	78.5°C	99.5°C	15	U1	62.8°C	81.8°C	16	U900	65.6°C	84.9°C	17	U201	69.1°C	88.9°C	18	T1core	80.5°C	101.9°C	19	CASE	49.0°C	67.6°C		P
NO	Position	ROOM AMBIENT Ta= 17.8 °C	HIGH AMBIENT Ta= 38.4 °C																																																																																		
1	LF2	60.0°C	79.1°C																																																																																		
2	Q2	66.1°C	85.1°C																																																																																		
3	Q1	64.3°C	83.3°C																																																																																		
4	BD1	63.5°C	82.2°C																																																																																		
5	D2	66.3°C	85.2°C																																																																																		
6	Q5	66.0°C	85.3°C																																																																																		
7	Q6	65.7°C	85.0°C																																																																																		
8	L1	66.1°C	84.9°C																																																																																		
9	C5	67.2°C	86.2°C																																																																																		
10	RTH2	62.4°C	81.4°C																																																																																		
11	TI Coil	73.6°C	93.3°C																																																																																		
12	Q102	73.2°C	93.0°C																																																																																		
13	C101	74.2°C	94.4°C																																																																																		
14	LF101	78.5°C	99.5°C																																																																																		
15	U1	62.8°C	81.8°C																																																																																		
16	U900	65.6°C	84.9°C																																																																																		
17	U201	69.1°C	88.9°C																																																																																		
18	T1core	80.5°C	101.9°C																																																																																		
19	CASE	49.0°C	67.6°C																																																																																		
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 230 VAC O/P : 120 % LOAD Ta : 25°C	TEST : OK	P																																																																																
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/100VAC O/P : 100 % LOAD Ta= -35 °C	TEST : OK	P																																																																																
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 40 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 40.6 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																																																
5	TEMPERATURE COEFFICIENT	± 0.03 %/°C (0-40°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.013 %/°C (0-40°C)	P																																																																																
6	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -40°C~ +85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																																																



7	THERMAL SHOCK TEST	1. Thermal shock Temperature : -30°C~ +70°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec	TEST : OK	P
8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10-500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 2G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK	P
9	CAPACITOR LIFE CYCLE	SUPPOSE C 101 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta= 40 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 40 °C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta= 40°C LIFE TIME	(1) 62893HRS (2) 22926HRS (3) 80180HRS (4) 271681HRS	P
10	MTBF	MIL-HDBK-217F TOTAL FAILURE RATE : 181.24 KHRS		P
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure (Expected Life): Above 30,000 hours @ TA 40°C		P

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	FRANK	GESG	WANGDZ

2007/3/20 A50-S014