



Test Report: GST36B12-P1J

36W AC-DC High Reliability Industrial Adaptor

DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|----------------------------------|----------------------------------|--|--|---------|
| 1 | RIPPLE & NOISE(Max) | V1: 100mVp-p | I/P: 230VAC O/P:FULL LOAD Ta:25°C | V1: 22.8mVp-p | P |
| 2 | OUTPUT VOLTAGE(Max) TOLERANCE | V1: 3%~ -3% | I/P: 100VAC /264VAC O/P:FULL/ MIN. LOAD Ta:25°C | V1: 1.667%~0% | P |
| 3 | LINE REGULATION (Max) | V1: 1%~ -1% | I/P: 100VAC~ 264VAC O/P:FULL LOAD Ta:25°C | V1: 0%~0% | P |
| 4 | LOAD REGULATION(Max) | V1: 3%~ -3% | I/P: 230VAC O/P:FULL ~MIN LOAD Ta:25°C | V1: 0.41%~0.487% | P |
| 5 | SET UP TIME(Max) | 230VAC/1000 ms 115VAC/1500 ms | I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C | 230VAC/ 592ms 115VAC/1108ms | P |
| 6 | RISE TIME (Max) | 230VAC/30ms 115VAC/30 ms | I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C | 230VAC/ 16.2ms 115VAC/ 16.2ms | P |
| 7 | HOLD UP TIME(Typ) | 230VAC/50 ms 115VAC/13 ms | I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C | 230VAC/ 64ms 115VAC/13.6ms | P |
| 8 | OVER/UNDERSHOOT TEST | < ±5% | I/P: 230VAC O/P:FULL LOAD Ta:25°C | < ±5% | P |
| 9 | DYNAMIC LOAD | V1: 1200 mVp-p | I/P: 230VAC O/P(1)FULL /Min LOAD 90%DUTY / 1KHZ (2) (1)FULL /Min LOAD 90%DUTY / 3KHZ (3)FULL /Min LOAD 90%DUTY / 5KHZ (4)FULL /Min LOAD 50%DUTY / 120HZ Ta:25°C | 311mVp-p 285mVp-p 286mVp-p 428mVp-p | P |

INPUT FUNCTION TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|-----------------------|------------------------------------|--|--------------------------------------|---------|
| 1 | INPUT VOLTAGE RANGE | 100VAC~264VAC | I/P:TESTING O/P:FULL LOAD Ta:25°C | 71V~264V | P |
| | | | I/P: (1)LOW-LINE-3V=97V HIGH-LINE+15%=300 V O/P:FULL/MIN LOAD ON: 30 Sec OFF: 30 Sec 10MIN (2)230Vac ON: 0.5 Sec OFF: 0.5 Sec 20MIN (3)230Vac ON:3Sec OFF:3Sec 12HOURS (POWER ON/OFF NO DAMAGE) | TEST:OK | |
| 2 | INPUT FREQUENCY RANGE | 47HZ ~63 HZ NO DAMAGE | I/P:100 VAC ~264 VAC O/P:FULL~MIN LOAD Ta:25°C | TEST: OK | P |
| 3 | EFFICIENCY(TYP) | 87.5% | I/P:230 VAC I/P:115 VAC O/P:FULL LOAD Ta:25°C | 89.11% | P |
| 4 | INPUT CURRENT (Typ) | 230V/ 0.45 A 115V/ 0.8 A | I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C | I =0.33A/ 230VAC I =0.56A/ 115VAC | P |
| 5 | INRUSH CURRENT(Typ) | 230V/70A 115V/35A COLD START | I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C | I =57.1A/230VAC I =28.6A/115VAC | P |
| 6 | LEAKAGE CURRENT | < 0.25 mA / 240 VAC | I/P : 240 VAC O/P : Min LOAD Ta : 25°C | L-FG : 0.001 mA N-FG : 0.001 mA | P |
| 7 | NO LOAD CONSUMPTION | < 0.075 W | I/P : 115VAC I/P : 230VAC O/P : NO LOAD Ta : 25°C | <0.0245W < 0.0332W | P |

PROTECTION FUNCTION TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|-------------------------|---|--|---|---------|
| 1 | OVER LOAD PROTECTION | 110 %~150% | I/P: 230VAC I/P: 115VAC O/P: TESTING Ta:25°C | 135.66%/ 230VAC 133.33%/115VAC Hiccup mode, recovers automatically after fault condition is removed | P |
| 2 | OVER VOLTAGE PROTECTION | 110 ~ 140% rated output voltage Clamp by zener diode | I/P: 230VAC I/P: 115VAC O/P: MIN LOAD Ta:25°C | 124.16%/ 230VAC 124.16%/115VAC Clamp by zener diode | P |
| 3 | SHORT PROTECTION | SHORT EVERY OUTPUT 1 HOUR NO DAMAGE | I/P: 264VAC O/P: FULL LOAD Ta:25°C | NO DAMAGE Hiccup mode, recovers automatically after fault condition is removed | P |

COMPONENT STRESS TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|--|---------------------------------|--|--|---------|
| 1 | PWM Transistor (D to S) or (C to E) Peak Voltage | Q 1 Rated :6A/600V | I/P: High-Line +3V =267V AC ON/OFF VDS: O/P: (1) Full Load (2) Output Short (3) Full Load Continue Ta:25°C | (1) 502V (2) 578V (3) 496V | P |
| 2 | Diode Peak Voltage | D100 Rated : 30A/ 100V | I/P: High-Line +3V =267 V AC ON/OFF O/P: (1) Full Load (2) Output Short (3) Dynamic Load Full Load/ Min. Load 90%Duty/5KHz (4) Dynamic Load 100% Load/ Min. Load 50%Duty/120Hz Ta:25°C | D100 : (1) 86.0V (2) 90.0V (3) 85.6V (4) 86.0V | P |
| 3 | Input Capacitor Voltage | C5 Rated: 56u/400V 105°C | I/P: High-Line +3V =267 V O/P: (1) Full Load input on/off (2) Min load input on /Off (3) Full Load /Min load Change Ta:25°C | (1) 376V (2) 366V (3) 366V | P |
| 4 | Control IC Voltage Test | PWM IC U1 Rated : 27V 10V(MIN.) | I/P: High-Line +3V =267 V AC ON/OFF O/P: (1) FULL LOAD (2) Output Short (3) O.L.P (4) NO LOAD VR MIN LOW LINE Ta:25°C | (1) 17.0V (2) 16.9V (3) 17.0V (4) 16.9V | P |

| | | | | | |
|---|--------------------------|---------------------|---|------------------------|---|
| 5 | Clamp Diode Peak Voltage | D1 Rated: : 2A/800V | I/P : High-Line +3V = 267 V AC ON/OFF O/P : (1) Dynamic Load 90%Duty/1KHz (2) Full load continue Ta : 25°C | (1) 432 V (2) 432 V | P |
|---|--------------------------|---------------------|---|------------------------|---|

SAFETY TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|----------------------|-------------------------|------------------------------------|------------------------------|---------|
| 1 | WITHSTAND VOLTAGE | I/P-O/P: 4.242 KVDC/min | I/P-O/P: 4.666 KVDC/min Ta:25°C | I/P-O/P:0.002mA NO DAMAGE | P |
| 2 | ISOLATION RESISTANCE | I/P-O/P:500VDC>100MΩ | I/P-O/P: 500 VDC Ta:25°C | I/P-O/P: 9999MΩ | P |

E.M.C TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT |
|----|---|--|--|-------------------------------|---------|
| 1 | HARMONIC | EN61000-3-2 CLASS A | I/P:230VAC/50HZ O/P:100%LOAD Ta:25°C | PASS | P |
| 2 | CONDUCTION | EN55022 CLASS B | I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C | PASS Test by certified Lab | P |
| 3 | RADIATION | EN55022 CLASS B | I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C | PASS Test by certified Lab | P |
| 4 | E.S.D | EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV | I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C | CRITERIA A | P |
| 5 | E.F.T | EN61000-4-4 LIGHT INDUSTRY INPUT : 1KV | I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C | CRITERIA A | P |
| 6 | SURGE | IEC61000-4-5 LIGHT INDUSTRY L-N : 1KV | I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C | CRITERIA A | P |
| 7 | Test by certified Lab & Test Report Prepare | | | | |

RELIABILITY TEST

ENVIRONMENT TEST

| NO | TEST ITEM | SPECIFICATION | TEST CONDITION | RESULT | VERDICT | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|----|---|--|--|-----------------|----------|---------------------------|---------------------------|---|-----------|--------|--------|---|------------|--------|--------|---|-----------|--------|--------|---|-----------|--------|--------|---|------------|--------|--------|---|-----------|--------|--------|---|-------------|--------|--------|---|-------------|--------|--------|---|------------|--------|--------|----|-----------|--------|--------|--|---|
| 1 | TEMPERATURE RISE TEST | MODEL : GST36B12-P1J 1. ROOM AMBIENT BURN-IN : 1HRS I/P : 230VAC O/P : FULL LOAD Ta=30.6°C 2. HIGH AMBIENT BURN-IN : 1 HRS I/P : 230VAC O/P : FULL LOAD Ta=47.0°C | <table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta=30.6°C</th> <th>HIGH AMBIENT Ta=47.0°C</th> </tr> </thead> <tbody> <tr><td>1</td><td>C5</td><td>66.6°C</td><td>80.8°C</td></tr> <tr><td>2</td><td>BD1</td><td>72.0°C</td><td>85.9°C</td></tr> <tr><td>3</td><td>T1</td><td>79.5°C</td><td>93.6°C</td></tr> <tr><td>4</td><td>Q1</td><td>81.9°C</td><td>97.0°C</td></tr> <tr><td>5</td><td>C40</td><td>72.7°C</td><td>86.5°C</td></tr> <tr><td>6</td><td>D1</td><td>80.9°C</td><td>95.5°C</td></tr> <tr><td>7</td><td>C105</td><td>74.9°C</td><td>89.3°C</td></tr> <tr><td>8</td><td>D100</td><td>85.5°C</td><td>99.7°C</td></tr> <tr><td>9</td><td>LF1</td><td>69.3°C</td><td>82.8°C</td></tr> <tr><td>10</td><td>TC</td><td>59.5°C</td><td>75.9°C</td></tr> </tbody> </table> | NO | Position | ROOM AMBIENT Ta=30.6°C | HIGH AMBIENT Ta=47.0°C | 1 | C5 | 66.6°C | 80.8°C | 2 | BD1 | 72.0°C | 85.9°C | 3 | T1 | 79.5°C | 93.6°C | 4 | Q1 | 81.9°C | 97.0°C | 5 | C40 | 72.7°C | 86.5°C | 6 | D1 | 80.9°C | 95.5°C | 7 | C105 | 74.9°C | 89.3°C | 8 | D100 | 85.5°C | 99.7°C | 9 | LF1 | 69.3°C | 82.8°C | 10 | TC | 59.5°C | 75.9°C | | P |
| NO | Position | ROOM AMBIENT Ta=30.6°C | HIGH AMBIENT Ta=47.0°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | C5 | 66.6°C | 80.8°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | BD1 | 72.0°C | 85.9°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | T1 | 79.5°C | 93.6°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | Q1 | 81.9°C | 97.0°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | C40 | 72.7°C | 86.5°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | D1 | 80.9°C | 95.5°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7 | C105 | 74.9°C | 89.3°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 8 | D100 | 85.5°C | 99.7°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 9 | LF1 | 69.3°C | 82.8°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 10 | TC | 59.5°C | 75.9°C | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2 | OVER LOAD BURN-IN TEST | NO DAMAGE 1 HOUR (MIN) | I/P : 230 VAC O/P : 133% LOAD Ta : 25°C | TEST : OK | P | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 3 | LOW TEMPERATURE TURN ON TEST | TURN ON AFTER 2 HOUR | I/P : 264VAC/100VAC O/P : 100 % LOAD Ta=-30°C | TEST : OK | P | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 4 | HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST | AFTER 12 HOURS IN CHAMBER ON CONTROL 50°C NO DAMAGE | I/P : 272 VAC O/P : FULL LOAD Ta=50°C HUMIDITY= 95 %R.H | TEST : OK | P | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 5 | TEMPERATURE COEFFICIENT | ±0.03%/°C (0~50°C) | I/P : 230 VAC O/P : FULL LOAD | ±0%/°C (0~50°C) | P | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 6 | STORAGE TEMPERATURE TEST | 1. Thermal shock Temperature : -40°C~ +85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC | | OK | P | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 7 | THERMAL SHOCK TEST | 1. Thermal shock Temperature : -30°C~ +70°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec | | OK | P | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



| | | | | |
|----|-----------------------------|---|--|---|
| 8 | VIBRATION TEST | 1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 2G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C | TEST : OK | P |
| 9 | CAPACITOR LIFE CYCLE | SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta=25°C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=50°C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta=50°C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta=50°C LIFE TIME | (1) 77837HRS (2) 25790HRS (3) 32321HRS (4) 54250HRS | P |
| 10 | MTBF | MIL-HDBK-217F TOTAL FAILURE RATE : 692.3KHRS | | P |
| 11 | DMTBF/Accelerated Life Test | Demonstration Mean Time Between Failure (Expected Life): Above 30,000 hours @ TA 50°C | | P |

| TEST RESULT | TESTER | REVIEW | APPROVAL |
|-------------|--------|--------|----------|
| PASS | FRANK | GESG | WANGDZ |

2007/3/20 A50-S014