



Test Report: HLG-80H-12

80W Single Output Switching Power Supply

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	RIPPLE & NOISE	V1 : 150 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 13.4 mVp-p (Max)
2	OUTPUT VOLTAGE ADJUST RANGE	CH1 : 10.8 V ~ 13.5 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	10.516 V ~ 13.784 V / 230 VAC 10.519 V ~ 13.785 V / 115 VAC
3	CURRENT ADJUST RANGE	CH1 : 3A ~ 5A	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	1.03 A ~ 5.696 A / 230 VAC 1.035 A ~ 5.713 A / 115 VAC
4	OUTPUT VOLTAGE TOLERANCE	V1 : 2.5 % ~ -2.5 % (Max)	I/P : 100 VAC / 305 VAC O/P : FULL / MIN LOAD Ta : 25°C	V1 : 0.4 % ~ -0.4 %
5	LINE REGULATION	V1 : 0.5 % ~ -0.5 % (Max)	I/P : 100VAC ~ 305 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0 % ~ 0 %
6	LOAD REGULATION	V1 : 0.5 % ~ -0.5 % (Max)	I/P : 230 VAC O/P : FULL ~ MIN LOAD Ta : 25°C	V1 : 0.4 % ~ -0.4 %
7	SET UP TIME	230VAC : 500 ms (Max) 115VAC : 1200 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 294 ms 115VAC/ 330 ms
8	RISE TIME	230VAC : 80 ms (Max) 115VAC : 80 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 19 ms 115VAC/ 16 ms
9	HOLD UP TIME	230VAC : 16 ms (TYP) 115VAC : 16 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 105 ms 115VAC/ 46 ms
10	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %
11	DYNAMIC LOAD	V1 : 1200 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1)341 mVp-p (2)563 mVp-p

12	DIMMER TEST (for B-type only)	SPEC:																																
		*Reference resistance value for output current adjustment (Typical)																																
		<table border="1"> <tr> <th>Resistance value</th> <th>10K</th> <th>20K</th> <th>30K</th> <th>40K</th> <th>50K</th> <th>60K</th> <th>70K</th> <th>80K</th> <th>90K</th> <th>100K</th> </tr> <tr> <th>Output current</th> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> </tr> </table>	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%										
		Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K																						
		Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																						
		*1 ~ 10V dimming function for output current adjustment (Typical)																																
		<table border="1"> <tr> <th>Dimming value</th> <th>1V</th> <th>2V</th> <th>3V</th> <th>4V</th> <th>5V</th> <th>6V</th> <th>7V</th> <th>8V</th> <th>9V</th> <th>10V</th> </tr> <tr> <th>Output current</th> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> </tr> </table>	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%										
		Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V																						
		Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																						
		*10V PWM signal for output current adjustment (Typical)																																
		<table border="1"> <tr> <th>Duty value</th> <th>10%</th> <th>20%</th> <th>30%</th> <th>40%</th> <th>50%</th> <th>60%</th> <th>70%</th> <th>80%</th> <th>90%</th> <th>100%</th> </tr> <tr> <th>Output current</th> <td>10%</td> <td>20%</td> <td>30%</td> <td>40%</td> <td>50%</td> <td>60%</td> <td>70%</td> <td>80%</td> <td>90%</td> <td>100%</td> </tr> </table>	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%										
		Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																						
Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																								
TEST RESULT: I/P : 230 VAC ; Ta : 25°C																																		
<table border="1"> <tr> <th rowspan="3">1</th> <th>Resistance value</th> <th>10K</th> <th>20K</th> <th>30K</th> <th>40K</th> <th>50K</th> <th>60K</th> <th>70K</th> <th>80K</th> <th>90K</th> <th>100K</th> </tr> <tr> <th>Output current</th> <td>0.661A</td> <td>1.030A</td> <td>1.501A</td> <td>2.011A</td> <td>2.582A</td> <td>3.067A</td> <td>3.548A</td> <td>4.047A</td> <td>4.602A</td> <td>5.109A</td> </tr> <tr> <th>%</th> <td>13.22%</td> <td>20.60%</td> <td>30.02%</td> <td>40.22%</td> <td>51.64%</td> <td>61.34%</td> <td>70.96%</td> <td>80.94%</td> <td>92.04%</td> <td>102.18%</td> </tr> </table>	1	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	Output current	0.661A	1.030A	1.501A	2.011A	2.582A	3.067A	3.548A	4.047A	4.602A	5.109A	%	13.22%	20.60%	30.02%	40.22%	51.64%	61.34%	70.96%	80.94%	92.04%	102.18%
1		Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K																						
		Output current	0.661A	1.030A	1.501A	2.011A	2.582A	3.067A	3.548A	4.047A	4.602A	5.109A																						
	%	13.22%	20.60%	30.02%	40.22%	51.64%	61.34%	70.96%	80.94%	92.04%	102.18%																							
<table border="1"> <tr> <th rowspan="3">2</th> <th>Dimming value</th> <th>1V</th> <th>2V</th> <th>3V</th> <th>4V</th> <th>5V</th> <th>6V</th> <th>7V</th> <th>8V</th> <th>9V</th> <th>10V</th> </tr> <tr> <th>Output current</th> <td>0.653A</td> <td>1.026A</td> <td>1.493A</td> <td>1.989A</td> <td>2.500A</td> <td>3.005A</td> <td>3.520A</td> <td>4.020A</td> <td>4.520A</td> <td>5.018A</td> </tr> <tr> <th>%</th> <td>13.06%</td> <td>20.52%</td> <td>29.86%</td> <td>39.78%</td> <td>50.00%</td> <td>60.10%</td> <td>70.40%</td> <td>80.40%</td> <td>90.40%</td> <td>100.36%</td> </tr> </table>	2	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	Output current	0.653A	1.026A	1.493A	1.989A	2.500A	3.005A	3.520A	4.020A	4.520A	5.018A	%	13.06%	20.52%	29.86%	39.78%	50.00%	60.10%	70.40%	80.40%	90.40%	100.36%
2		Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V																						
		Output current	0.653A	1.026A	1.493A	1.989A	2.500A	3.005A	3.520A	4.020A	4.520A	5.018A																						
	%	13.06%	20.52%	29.86%	39.78%	50.00%	60.10%	70.40%	80.40%	90.40%	100.36%																							
<table border="1"> <tr> <th rowspan="3">3</th> <th>Duty value</th> <th>10%</th> <th>20%</th> <th>30%</th> <th>40%</th> <th>50%</th> <th>60%</th> <th>70%</th> <th>80%</th> <th>90%</th> <th>100%</th> </tr> <tr> <th>Output current</th> <td>0.548A</td> <td>1.062A</td> <td>1.432A</td> <td>1.943A</td> <td>2.481A</td> <td>3.018A</td> <td>3.554A</td> <td>4.073A</td> <td>4.593A</td> <td>5.126A</td> </tr> <tr> <th>%</th> <td>10.96%</td> <td>21.24%</td> <td>28.64%</td> <td>38.86%</td> <td>49.62%</td> <td>60.36%</td> <td>71.08%</td> <td>81.46%</td> <td>91.86%</td> <td>102.52%</td> </tr> </table>	3	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Output current	0.548A	1.062A	1.432A	1.943A	2.481A	3.018A	3.554A	4.073A	4.593A	5.126A	%	10.96%	21.24%	28.64%	38.86%	49.62%	60.36%	71.08%	81.46%	91.86%	102.52%
3		Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																						
		Output current	0.548A	1.062A	1.432A	1.943A	2.481A	3.018A	3.554A	4.073A	4.593A	5.126A																						
	%	10.96%	21.24%	28.64%	38.86%	49.62%	60.36%	71.08%	81.46%	91.86%	102.52%																							

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	90VAC~305 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C I/P : LOW-LINE-3V= 87 V HIGH-LINE+15%=305 V O/P : FULL/MIN LOAD ON : 30 Sec. OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	67 V~305V TEST : OK
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P : 90 VAC ~ 305 VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK
3	POWER FACTOR	0.96 / 230 VAC(TYP) 0.96 / 115 VAC(TYP) 0.94 / 277 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.964 / 230 VAC PF= 0.989 / 115 VAC PF= 0.945 / 277 VAC
4	EFFICIENCY	88 % (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	89.2 %

5	INPUT CURRENT	277V/ 0.4 A (TYP) 230V/ 0.425 A (TYP) 115V/ 0.85 A (TYP)	I/P : 277 VAC I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 0.26 A/ 277 VAC I = 0.3 A/ 230 VAC I = 0.59 A/ 115 VAC
6	INRUSH CURRENT	230V/ 70 A (TYP) COLD START	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I = 65 A/ 230 VAC
7	LEAKAGE CURRENT	< 0.75 mA / 277 VAC	I/P : 277 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.18 mA N-FG : 0.18 mA
8	TOTAL HARMONIC DISTORTION	THD < 20% when output loading ≥ 60% at 115VAC/230VAC input and output loading ≥ 75% at 277VAC input	I/P : 115 VAC I/P : 230 VAC O/P : 60% LOAD I/P : 277 VAC O/P : 75%LOAD Ta : 25°C	THD : 9.59 /115VAC THD : 15.64 /230VAC THD : 15.53 /277VAC

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER LOAD PROTECTION	95 % ~ 108 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	101.6 % / 230 VAC 101.8 % / 115 VAC Constant current limiting, recovers automatically after fault condition is removed
2	OVER VOLTAGE PROTECTION	CH1 : 14 V ~ 17 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	15.966 V / 230 VAC 16.079 V / 115 VAC Shut down o/p voltage, re-power on to recover
3	OVER TEMPERATURE PROTECTION	NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage, re-power on to recover
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 305 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Constant current limiting, recovers automatically after fault condition is removed

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 1 Rated : 12A/700V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 640 V (2) 528 V (3) 636 V
2	Diode Peak Voltage	Q101 Rated : 84A/60V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 57 V (2) 54.8 V (3) 57 V
3	Clamp Diode Peak Voltage	D12 Rated : 2A/800V	I/P : High-Line +3V = 308 V O/P : (1) Dynamic Load 90%Duty/1KHz (2)Full load continue Ta : 25°C	(1) 616 V (2) 608 V
4	Input Capacitor Voltage	C 5 Rated : 82u/450V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 424.65 V (2) 435.61 V (3) 434.90 V
5	Control IC Voltage Test	U1 Rated : 16V~38V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 21.868 V (2) 21.626 V (3) 21.621 V
6	Power Transistor (D to S) or (C to E) Peak Voltage	Q2 Rated : 10A/600V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 500 V (2) 464 V (3) 456 V

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.75 KVAC/min I/P-FG : 2KVAC/min<4.5mA O/P-FG : 1.5 KVAC/min	I/P-O/P : 4 KVAC/min I/P-FG : 2.4KVAC/min O/P-FG : 1.8 KVAC/min Ta : 25°C	I/P-O/P : 1.689 mA I/P-FG : 1.895 mA O/P-FG : 0.299 mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C /70%RH	I/P-O/P : 11.3 GΩ I/P-FG : 30 GΩ O/P-FG : 30 GΩ NO DAMAGE
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	9 mΩ
4	APPROVAL	TUV : Certificate NO : R50202516 UL : File NO : E334687		

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	EN61000-3-2 CLASS A CLASS C	I/P: 230VAC/50HZ O/P:100% ELECTRONICLOAD O/P:100%LED LOAD Ta:25°C	PASS
2	CONDUCTION	EN55015 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab
3	RADIATION	EN55015 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab
4	E.S.D	EN61000-4-2 INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A
5	E.F.T	EN61000-4-4 INDUSTRY INPUT: 2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A
6	SURGE	IEC61000-4-5 INDUSTRY L-N :2KV L,N-PE:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																				
1	TEMPERATURE RISE TEST	MODEL : HLG-80H-12 1. ROOM AMBIENT BURN-IN : 13.5 HRS I/P : 230VAC O/P : 95% LOAD Ta=25.1℃ 2. HIGH AMBIENT BURN-IN : 67 HRS I/P : 230VAC O/P : 95% LOAD Ta=63.8℃	<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 25.1 ℃</th> <th>HIGH AMBIENT Ta=63.8 ℃</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>44.9℃</td><td>77.0℃</td></tr> <tr><td>2</td><td>BD1</td><td>49.3℃</td><td>81.2℃</td></tr> <tr><td>3</td><td>L1</td><td>48.4℃</td><td>79.8℃</td></tr> <tr><td>4</td><td>C5</td><td>48.4℃</td><td>79.8℃</td></tr> <tr><td>5</td><td>Q1</td><td>52.2℃</td><td>84.1℃</td></tr> <tr><td>6</td><td>Q2</td><td>49.9℃</td><td>81.8℃</td></tr> <tr><td>7</td><td>U1</td><td>46.4℃</td><td>78.4℃</td></tr> <tr><td>8</td><td>RTH2</td><td>47.0℃</td><td>78.7℃</td></tr> <tr><td>9</td><td>T1</td><td>52.6℃</td><td>84.0℃</td></tr> <tr><td>10</td><td>Q101</td><td>51.1℃</td><td>83.6℃</td></tr> <tr><td>11</td><td>C106</td><td>49.3℃</td><td>81.3℃</td></tr> <tr><td>12</td><td>L100</td><td>47.2℃</td><td>79.5℃</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 25.1 ℃	HIGH AMBIENT Ta=63.8 ℃	1	LF1	44.9℃	77.0℃	2	BD1	49.3℃	81.2℃	3	L1	48.4℃	79.8℃	4	C5	48.4℃	79.8℃	5	Q1	52.2℃	84.1℃	6	Q2	49.9℃	81.8℃	7	U1	46.4℃	78.4℃	8	RTH2	47.0℃	78.7℃	9	T1	52.6℃	84.0℃	10	Q101	51.1℃	83.6℃	11	C106	49.3℃	81.3℃	12	L100	47.2℃	79.5℃	
NO	Position	ROOM AMBIENT Ta= 25.1 ℃	HIGH AMBIENT Ta=63.8 ℃																																																					
1	LF1	44.9℃	77.0℃																																																					
2	BD1	49.3℃	81.2℃																																																					
3	L1	48.4℃	79.8℃																																																					
4	C5	48.4℃	79.8℃																																																					
5	Q1	52.2℃	84.1℃																																																					
6	Q2	49.9℃	81.8℃																																																					
7	U1	46.4℃	78.4℃																																																					
8	RTH2	47.0℃	78.7℃																																																					
9	T1	52.6℃	84.0℃																																																					
10	Q101	51.1℃	83.6℃																																																					
11	C106	49.3℃	81.3℃																																																					
12	L100	47.2℃	79.5℃																																																					
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 305VAC/100VAC O/P : 95% LOAD Ta= -40℃ / -25	TEST : OK																																																				
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60 ℃ NO DAMAGE	I/P : 305 VAC O/P : 95% LOAD Ta= 60 ℃ HUMIDITY= 95%R.H	TEST : OK																																																				
4	TEMPERATURE COEFFICIENT	± 0.03 % (0~50℃)	I/P : 230 VAC O/P : 95% LOAD	± 0.02 % (0~50℃)																																																				
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45℃~ +90℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK																																																				
6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -30℃~ +65℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec		OK																																																				



7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 5G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK
8	CAPACITOR LIFE CYCLE	HLG-80H-12:SUPPOSE C106 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta=25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=60 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 60 °C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta= 60 °C LIFE TIME	(1) 531024HRS (2) 74703HRS (3) 86358HRS (4) 112443HRS
9	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE : 357.8 KHRS	
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 62,000 hours @ Tcase 75°C	

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2010/11/5	RD SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2010/12/24	PRODUCT SAMPLE	PASS	SANFORD SU	VINCENT TSENG

2009/08/04 A50-F023