



Test Report : HSP-200-5

200W Single Output with PFC Function

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

ENVIRONMENT TEST

■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 150 mVp-p (Max)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	V1 : 92 mVp-p (Max)	PASS
2	OUTPUT VOLTAGE ADJUST RANGE	V1 : 4.5 V ~ 5.5 V	I/P : 115 VAC O/P : NO LOAD Ta : 25°C	V1 : 4.369V~ 5.688V	PASS
3	OUTPUT VOLTAGE TOLERANCE	V1 : -2.0 %~ 2.0 % (Max)	I/P : 100 VAC / 264 VAC O/P : FULL/ NO LOAD Ta : 25°C	V1 : -0.75 %~ 1.42 %	PASS
4	LINE REGULATION	V1 : -0.5 %~ 0.5 % (Max)	I/P : 100 VAC ~ 264 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0.01 %~ 0 %	PASS
5	LOAD REGULATION	V1 : -1.0 %~ 1.0 % (Max)	I/P : 230 VAC O/P : FULL~NO LOAD Ta : 25°C	V1 : -0.32 %~ 0.33 %	PASS
6	SET UP TIME	115VAC : 3000 ms (Max) 230VAC : 2000 ms(Max)	I/P : 115 VAC I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	115VAC/ 1980 ms 230VAC/ 1245 ms	PASS
7	RISE TIME	115VAC : 200 ms (Max) 230VAC : 200 ms (Max)	I/P : 115 VAC I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	115VAC/ 89 ms 230VAC/ 115 ms	PASS
8	HOLD UP TIME	115VAC : 16 ms (TYP) 230VAC : 16 ms (TYP)	I/P : 115 VAC I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	115VAC/ 26 ms 230VAC/ 26 ms	PASS
9	OVER/UNDERSHOOT TEST	< ±10%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : < 10 %	PASS
10	DYNAMIC LOAD	V1 : 1000 mVp-p	I/P : 230 VAC (1).O/P : FULL /NO LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /NO LOAD 50%DUTY/ 120HZ Ta : 25°C	(1) 644 mVp-p (2) 892 mVp-p	PASS

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	90 VAC~264 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	87V~264 V	PASS
			I/P : (1)LOW-LINE-3V=87 V HIGH-LINE+15%=300 V O/P : FULL/NO LOAD ON : 30 Sec OFF : 30 Sec 10MIN (2)230VAC ON : 0.5 Sec OFF : 0.5 Sec 20MIN (3)230VAC ON : 3Sec OFF : 3Sec 12HOURS (POWER ON/OFF NO DAMAGE)	TEST : (1) OK (2) OK (3) OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 90 VAC ~ 264 VAC O/P : FULL ~NO LOAD Ta : 25°C	TEST : OK	PASS
3	POWER FACTOR	115V/ 0.98 (TYP) 230V/ 0.95 (TYP)	I/P : 115 VAC I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.996 / 115 VAC PF= 0.975 / 230 VAC	PASS
4	EFFICIENCY	88.5% (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	89.01%	PASS
5	INPUT CURRENT	115V/ 3.0 A (TYP) 230V/ 2.0 A (TYP)	I/P : 115 VAC I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I = 2.033 A / 115 VAC I = 1.006 A / 230 VAC	PASS
6	INRUSH CURRENT	230V/ 70 A (TYP) COLD START	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I = 57.6 A	PASS
7	LEAKAGE CURRENT	< 1.0 mA / 240 VAC	I/P : 264 VAC O/P : NO LOAD Ta : 25°C	L-FG : 0.338 mA N-FG : 0.337 mA	PASS

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110 % ~ 140 %	I/P : 100 VAC I/P : 230 VAC I/P : 264 VAC O/P : TESTING Ta : 25°C	128.79 %/ 100 VAC 129.52 %/ 230 VAC 129.52 %/ 264 VAC Hiccup mode, recovers automatically after fault condition is removed	PASS
2	OVER VOLTAGE PROTECTION	CH1 : 5.6 V ~ 7.0 V	I/P : 90 VAC I/P : 230 VAC I/P : 264 VAC O/P : NO LOAD Ta : 25°C	6.07 V/ 90 VAC 6.12 V/ 230 VAC 6.11 V/ 264 VAC Hiccup mode, recovers automatically after fault condition is removed	PASS
3	OVER TEMPERATURE PROTECTION	SPEC : O.T.P. NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down O/P voltage, recovers automatically after fault condition is removed	PASS
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 264 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup mode, recovers automatically after fault condition is removed	PASS

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q3 Rated 600 V 11A	I/P : High-Line +3V = 267 V O/P : (1)FULL LOAD Turn on (2) Output Short (3) FULL LOAD continue Ta : 25°C	(1) 444 V (2) 440 V (3) 443 V	PASS
2	Diode Peak Voltage	Q101 Rated 40 V/32 A Q102 Rated 40V/120A	I/P : High-Line +3V = 267V O/P : (1) FULL LOAD Turn on (2)Output Short (3) FULL LOAD continue Ta : 25°C	Q101 (1) 17.9 V (2) 19.3 V (3) 18.2 V Q102 (1) 17.4 V (2) 17.0 V (3) 17.2 V	PASS
3	Input Capacitor Voltage	C5 Rated 120uF / 450 V	I/P : High-Line +3V = 267 V O/P : (1) FULL LOAD Turn on /Off (2) NO LOAD Turn on /Off (3) FULL LOAD /NO LOAD Change Ta : 25°C	(1) 448 V (2) 446 V (3) 448 V	PASS
4	Control IC Voltage Test	U2 Rated 30V	I/P : High-Line +3V = 267 V O/P : (1) FULL LOAD Turn on /Off (2) NO LOAD Turn on /Off (3) FULL LOAD /NO LOAD Change Ta : 25°C	(1) 20.4 V (2) 20.4 V (3) 20.3 V	PASS
5	PFC Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated 600 V 16A	I/P : High-Line +3V = 267V O/P : (1)FULL LOAD Turn on (2) Output Short (3) FULL LOAD continue Ta : 25°C	(1) 498 V (2) 490 V (3) 494 V	PASS

■ SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.0 KVAC/min I/P-FG : 2.0 KVAC/min O/P-FG : 0.5 KVAC/min	I/P-O/P : 3.6 KVAC/min I/P-FG : 2.4 KVAC/min O/P-FG : 0.6 KVAC/min Ta : 25°C	I/P-O/P : 1.798mA I/P-FG : 2.393mA O/P-FG : 1.421mA NO DAMAGE	PASS
2	ISOLATION RESISTANCE	I/P-O/P : 500V>100MΩ I/P-FG : 500V>100MΩ O/P-FG : 500V>100MΩ	I/P-O/P : 500 VDC Ta : 25°C/70%RH	I/P-O/P : >9999 MΩ I/P-FG : >9999 MΩ O/P-FG : >9999MΩ NO DAMAGE	PASS
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40A / 2min Ta : 25°C	5 mΩ	PASS

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																																
1	TEMPERATURE RISE TEST	MODEL : HSP-200-5 1. ROOM AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta=28.8 °C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta=54.4 °C			PASS																																																																																																
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 28.8 °C</th> <th>HIGH AMBIENT Ta= 54.4 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>L2</td><td>59.6°C</td><td>81.8°C</td></tr> <tr><td>2</td><td>C9</td><td>53.2°C</td><td>76.8°C</td></tr> <tr><td>3</td><td>RTH1</td><td>67.4°C</td><td>84.5°C</td></tr> <tr><td>4</td><td>Q1</td><td>50.6°C</td><td>75.3°C</td></tr> <tr><td>5</td><td>C5</td><td>60.4°C</td><td>83.6°C</td></tr> <tr><td>6</td><td>C35</td><td>66.8°C</td><td>89.2°C</td></tr> <tr><td>7</td><td>D16</td><td>69.3°C</td><td>91.6°C</td></tr> <tr><td>8</td><td>D3</td><td>59.9°C</td><td>82.8°C</td></tr> <tr><td>9</td><td>Q3</td><td>63.7°C</td><td>88.2°C</td></tr> <tr><td>10</td><td>Q4</td><td>59.7°C</td><td>84.1°C</td></tr> <tr><td>11</td><td>T1</td><td>83.2°C</td><td>106.6°C</td></tr> <tr><td>12</td><td>Q103</td><td>55.0°C</td><td>79.9°C</td></tr> <tr><td>13</td><td>Q102</td><td>52.9°C</td><td>77.8°C</td></tr> <tr><td>14</td><td>C38</td><td>61.1°C</td><td>83.4°C</td></tr> <tr><td>15</td><td>C105</td><td>70.3°C</td><td>95.7°C</td></tr> <tr><td>16</td><td>C108</td><td>66.2°C</td><td>92.7°C</td></tr> <tr><td>17</td><td>Q101</td><td>77.9°C</td><td>102.2°C</td></tr> <tr><td>18</td><td>Q100</td><td>76.4°C</td><td>101.1°C</td></tr> <tr><td>19</td><td>U2</td><td>62.6°C</td><td>85.9°C</td></tr> <tr><td>20</td><td>L100</td><td>77.9°C</td><td>102.7°C</td></tr> <tr><td>21</td><td>TSW1</td><td>49.5°C</td><td>74.2°C</td></tr> <tr><td>22</td><td>TC</td><td>47.4°C</td><td>71.9°C</td></tr> <tr><td>23</td><td>ZNR1</td><td>49.8°C</td><td>72.9°C</td></tr> </tbody> </table>	NO	Position		ROOM AMBIENT Ta= 28.8 °C	HIGH AMBIENT Ta= 54.4 °C	1	L2	59.6°C	81.8°C	2	C9	53.2°C	76.8°C	3	RTH1	67.4°C	84.5°C	4	Q1	50.6°C	75.3°C	5	C5	60.4°C	83.6°C	6	C35	66.8°C	89.2°C	7	D16	69.3°C	91.6°C	8	D3	59.9°C	82.8°C	9	Q3	63.7°C	88.2°C	10	Q4	59.7°C	84.1°C	11	T1	83.2°C	106.6°C	12	Q103	55.0°C	79.9°C	13	Q102	52.9°C	77.8°C	14	C38	61.1°C	83.4°C	15	C105	70.3°C	95.7°C	16	C108	66.2°C	92.7°C	17	Q101	77.9°C	102.2°C	18	Q100	76.4°C	101.1°C	19	U2	62.6°C	85.9°C	20	L100	77.9°C	102.7°C	21	TSW1	49.5°C	74.2°C	22	TC	47.4°C	71.9°C	23	ZNR1	49.8°C	72.9°C		
NO	Position	ROOM AMBIENT Ta= 28.8 °C	HIGH AMBIENT Ta= 54.4 °C																																																																																																		
1	L2	59.6°C	81.8°C																																																																																																		
2	C9	53.2°C	76.8°C																																																																																																		
3	RTH1	67.4°C	84.5°C																																																																																																		
4	Q1	50.6°C	75.3°C																																																																																																		
5	C5	60.4°C	83.6°C																																																																																																		
6	C35	66.8°C	89.2°C																																																																																																		
7	D16	69.3°C	91.6°C																																																																																																		
8	D3	59.9°C	82.8°C																																																																																																		
9	Q3	63.7°C	88.2°C																																																																																																		
10	Q4	59.7°C	84.1°C																																																																																																		
11	T1	83.2°C	106.6°C																																																																																																		
12	Q103	55.0°C	79.9°C																																																																																																		
13	Q102	52.9°C	77.8°C																																																																																																		
14	C38	61.1°C	83.4°C																																																																																																		
15	C105	70.3°C	95.7°C																																																																																																		
16	C108	66.2°C	92.7°C																																																																																																		
17	Q101	77.9°C	102.2°C																																																																																																		
18	Q100	76.4°C	101.1°C																																																																																																		
19	U2	62.6°C	85.9°C																																																																																																		
20	L100	77.9°C	102.7°C																																																																																																		
21	TSW1	49.5°C	74.2°C																																																																																																		
22	TC	47.4°C	71.9°C																																																																																																		
23	ZNR1	49.8°C	72.9°C																																																																																																		
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/100VAC O/P : FULL LOAD Ta= -35°C	TEST : OK	PASS																																																																																																

3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 50 °C HUMIDITY= 95% R.H	TEST : OK	PASS
4	TEMPERATURE COEFFICIENT	±0.03 %(0~60°C)	I/P : 230 VAC O/P : FULL LOAD	±0.012 %(0~60°C)	PASS
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	PASS
6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -35°C~ +55°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/FULL LOAD AC ON/OFF TEST turn on 58sec ; turn off 2sec		OK	PASS
7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 10min/sweep cycle (4) Acceleration : 3G (5) Test Time : 90min in each axis (X.Y.Z) (6) Ta : 25°C		TEST : OK	PASS
8	CAPACITOR LIFE CYCLE	HSP-200-5 : SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta=25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=50 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta=50 °C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta=50 °C LIFE TIME		(1) 165974 HRS (2) 29695 HRS (3) 66527 HRS (4) 114984 HRS	PASS
9	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE : 204KHRS			PASS
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 30000 hours @ Tcase 65°C			PASS

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	ZHOUB/ ZHUOKB	SKY	LIUWY

2009/08/04 A50-G058