



Test Report: IDLV-25-60

25W PWM Output LED Driver

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test



E.M.C. Test

■ RELIABILITY TEST

Environment Test


■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM FREQUENCY	1KHz (±20%)	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	1104Hz
2	VOLTAGE TOLERANCE	±10%	I/P: 90 VAC / 295 VAC O/P: FULL/ NO LOAD Ta: 25°C	-0.213%~+0.465%
3	OVER/UNDERSHOOT TEST	<±10%	I/P: 230VAC O/P: FULL LOAD Ta: 25°C	<±10%
4	SET UP TIME(Max)	500ms/230VAC 1200ms/115VAC	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	304ms/230VAC 824ms/115VAC
INPUT=230VAC/50HZ @ FULL LOAD CH1: Output Voltage CH2: AC Input Voltage				
INPUT=115VAC/60HZ @ FULL LOAD CH1: Output Voltage CH2: AC Input Voltage				
5	AUXILIARY DC OUTPUT (For A-Type only)	Nominal 12V (deviation 11.4~12.6) @50mA	I/P: 230 VAC O/P: FULL LOAD	11.89V

6 DIMMING TEST

※ Dimming principle for PWM style output
Dimming is achieved by varying the duty cycle of the output current.





$$\text{Duty cycle(\%)} = \frac{T_{ON}}{T} \times 100\%$$



Output PWM frequency : 1KHz(±20%)

※ 2 in 1 dimming function

● Applying additive 0 ~ 10VDC



● Applying additive 10V PWM signal (frequency range 300~3000Hz):



Note : 1. Min. duty cycle of output current is about 8% and the output current is not defined when 0% < Iout < 8%.
2. The duty cycle of output current could drop down to 0% when dimming input is about 0Vdc or 10V PWM signal with 0% duty cycle.

I/P: 230 VAC
O/P: DIMMING TEST
Ta: 25°C

1	Dimming voltage	0V	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	OPEN
	Output Current	0	0.05A	0.09A	0.13A	0.17A	0.21A	0.26A	0.30A	0.34A	0.38A	0.41A	0.41A
	Duty cycle of output current	0%	11.9%	21.4%	30.9%	40.5%	50.0%	61.9%	71.4%	81.0%	90.5%	97.6%	97.6%
2	Dimming Duty cycle	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	OPEN
	Output Current	0	0.05A	0.09A	0.13A	0.17A	0.26A	0.26A	0.30A	0.34A	0.38A	0.41A	0.42A
	Duty cycle of output current	0%	11.9%	21.4%	30.9%	40.5%	61.9%	61.9%	71.4%	81.0%	90.5%	97.6%	100.0%

TEST RESULT: OK




INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	90VAC-295VAC	I/P: TESTING O/P: FULL LOAD Ta: 25°C	87V-298V
			I/P: (1)LOW-LINE-3V=87 V HIGH-LINE+10V=305 V O/P: FULL/NO LOAD ON: 30 Sec OFF: 30 Sec 10MIN (2)230VAC ON: 0.5 Sec OFF: 0.5 Sec 20MIN (POWER ON/OFF NO DAMAGE)	TEST: OK
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P: 90 VAC ~295 VAC O/P: FULL-NO LOAD Ta: 25°C	TEST: OK
3	AC CURRENT	0.4A/115VAC 0.16A/230VAC 0.13A/277VAC	I/P: 115 VAC I/P: 230 VAC I/P: 277 VAC O/P: FULL LOAD Ta: 25°C	I = 0.2591A/ 115VAC I = 0.1319A/ 230VAC I = 0.1146A/ 277VAC
4	LEAKAGE CURRENT	< 0.75mA / 277VAC	I/P: 277 VAC O/P: NO LOAD Ta: 25°C	L-FG: 0.0047 mA N-FG: 0.0047 mA
5	NO LOAD POWER CONSUMPTION	< 0.5W for Blank-Type < 1.2W for A-Type	I/P: 230VAC O/P: NO LOAD Ta: 25°C	0.4122W for Blank-Type 0.4755W for A-Type
6	INRUSH CURRENT(Typ)	COLD START 30A/230VAC Twidth =150 us measured at 50% Ipeak	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	I=24.1A/ 230VAC Twidth = 90.4us

INPUT=230VAC/50HZ @ FULL LOAD

CH2: Input current CH1: AC Input Voltage






25W PWM Output LED Driver

IDLV-25 series


7	POWER FACTOR	0.95/ 115VAC 0.92/ 230VAC 0.9/ 277VAC	I/P: 115 VAC I/P: 230 VAC I/P: 277 VAC O/P: FULL LOAD Ta: 25°C	PF=0.996 /115VAC PF=0.976 /230VAC PF=0.942 /277VAC
---	--------------	---	--	--

PF vs LOAD




8	TOTAL HARMONIC DISTORTION	THD < 20% (@load ≥ 70%/115VAC, 230VAC; @load ≥ 75%/277VAC)	I/P: 115 VAC I/P: 230 VAC I/P: 277 VAC O/P: 70% /75% LOAD Ta: 25°C	THD=5.47% @70% load /115VAC THD=9.48% @70% load /230VAC THD=12.84% @75% load /277VAC
---	---------------------------	--	--	--

THD vs LOAD



9	EFFICIENCY(Typ)	84%	I/P: 230VAC O/P: FULL LOAD Ta: 25°C	86.95%
---	-----------------	-----	---	--------

EFFICIENCY vs LOAD





PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER CURRENT PROTECTION	105 %~ 120 %	I/P: 100VAC I/P: 230VAC I/P: 295VAC O/P: TESTING Ta: 25°C	112%/ 100VAC 112%/ 230VAC 112%/ 295VAC Hiccup mode, recovers automatically after fault condition is removed
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 90VAC I/P: 295VAC O/P: 70%/FULL LOAD Ta: 25°C	NO DAMAGE Shut down O/P voltage, re-power on to recovery

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated 7A/800V	I/P: High-Line +3V =298V O/P: (1) Full Load Turn on (2) Output Short (3) Full load continue Ta: 25°C	(1) 593V (2) 561V (3) 565V
2	Diode Peak Voltage	D100 Rated 5A/600V	I/P: High-Line +3V =298V O/P: (1) Full Load Turn on (2) Output Short (3) Full load continue Ta: 25°C	(1) 344V (2) 352V (3) 340V
3	Control IC Voltage Test	U1 Rated 35V	I/P: High-Line +3V =298V O/P: (1) Full Load input on/off (2) NO load input on /Off (3) Full Load /NO load Change Ta: 25°C	(1) 14.0V (2) 13.9V (3) 14.2V



SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P: 3.75KVAC/min	I/P-O/P: 4.125KVAC/min Ta: 25°C	I/P-O/P: 1.697mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P: 500VDC>100MΩ	I/P-O/P: 500VDC Ta: 25°C	I/P-O/P: >9999MΩ

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	EN61000-3-2	I/P: 230VAC/50HZ O/P: FULL /70% LOAD Ta: 25°C	PASS
2	CONDUCTION	EN55015	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
3	RADIATION	EN55015	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY Air: 8KV Contact: 4KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
6	SURGE	EN61000-4-5 LIGHT INDUSTRY L-N: 1KV	I/P: 230VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
7	Test by certified Lab & Test Report Prepare			

■ **RELIABILITY TEST**

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																																																				
1	TEMPERATURE RISE TEST	MODEL: IDLV-25-36 1. ROOM AMBIENT BURN-IN: 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 24.4℃ 2. HIGH AMBIENT BURN-IN: 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 45.6℃																																																																																						
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 24.4 °C</th> <th>HIGH AMBIENT Ta=45.6 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>BD1</td><td>62.9℃</td><td>81.3℃</td></tr> <tr><td>2</td><td>L1</td><td>46.2℃</td><td>65.7℃</td></tr> <tr><td>3</td><td>RTH1</td><td>49.5℃</td><td>68.5℃</td></tr> <tr><td>4</td><td>C8</td><td>72.3℃</td><td>90.5℃</td></tr> <tr><td>5</td><td>C6</td><td>69.7℃</td><td>88.1℃</td></tr> <tr><td>6</td><td>Q1</td><td>76.0℃</td><td>94.9℃</td></tr> <tr><td>7</td><td>D1</td><td>75.5℃</td><td>94.1℃</td></tr> <tr><td>8</td><td>U1</td><td>69.3℃</td><td>88.1℃</td></tr> <tr><td>9</td><td>C16</td><td>69.0℃</td><td>87.1℃</td></tr> <tr><td>10</td><td>T1</td><td>71.6℃</td><td>89.3℃</td></tr> <tr><td>11</td><td>D100</td><td>68.5℃</td><td>86.6℃</td></tr> <tr><td>12</td><td>Q100</td><td>56.2℃</td><td>75.3℃</td></tr> <tr><td>13</td><td>U100</td><td>65.5℃</td><td>83.7℃</td></tr> <tr><td>14</td><td>RG1</td><td>74.3℃</td><td>92.6℃</td></tr> <tr><td>15</td><td>C206</td><td>59.6℃</td><td>77.9℃</td></tr> <tr><td>16</td><td>C105</td><td>54.9℃</td><td>73.7℃</td></tr> <tr><td>17</td><td>C106</td><td>58.4℃</td><td>76.7℃</td></tr> <tr><td>18</td><td>LF100</td><td>47.9℃</td><td>67.3℃</td></tr> <tr><td>19</td><td>THS2</td><td>58.5℃</td><td>76.9℃</td></tr> <tr><td>20</td><td>TC</td><td>57.1℃</td><td>75.6℃</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 24.4 °C	HIGH AMBIENT Ta=45.6 °C	1	BD1	62.9℃	81.3℃	2	L1	46.2℃	65.7℃	3	RTH1	49.5℃	68.5℃	4	C8	72.3℃	90.5℃	5	C6	69.7℃	88.1℃	6	Q1	76.0℃	94.9℃	7	D1	75.5℃	94.1℃	8	U1	69.3℃	88.1℃	9	C16	69.0℃	87.1℃	10	T1	71.6℃	89.3℃	11	D100	68.5℃	86.6℃	12	Q100	56.2℃	75.3℃	13	U100	65.5℃	83.7℃	14	RG1	74.3℃	92.6℃	15	C206	59.6℃	77.9℃	16	C105	54.9℃	73.7℃	17	C106	58.4℃	76.7℃	18	LF100	47.9℃	67.3℃	19	THS2	58.5℃	76.9℃	20	TC	57.1℃	75.6℃		
NO	Position	ROOM AMBIENT Ta= 24.4 °C	HIGH AMBIENT Ta=45.6 °C																																																																																					
1	BD1	62.9℃	81.3℃																																																																																					
2	L1	46.2℃	65.7℃																																																																																					
3	RTH1	49.5℃	68.5℃																																																																																					
4	C8	72.3℃	90.5℃																																																																																					
5	C6	69.7℃	88.1℃																																																																																					
6	Q1	76.0℃	94.9℃																																																																																					
7	D1	75.5℃	94.1℃																																																																																					
8	U1	69.3℃	88.1℃																																																																																					
9	C16	69.0℃	87.1℃																																																																																					
10	T1	71.6℃	89.3℃																																																																																					
11	D100	68.5℃	86.6℃																																																																																					
12	Q100	56.2℃	75.3℃																																																																																					
13	U100	65.5℃	83.7℃																																																																																					
14	RG1	74.3℃	92.6℃																																																																																					
15	C206	59.6℃	77.9℃																																																																																					
16	C105	54.9℃	73.7℃																																																																																					
17	C106	58.4℃	76.7℃																																																																																					
18	LF100	47.9℃	67.3℃																																																																																					
19	THS2	58.5℃	76.9℃																																																																																					
20	TC	57.1℃	75.6℃																																																																																					
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 295VAC/100VAC O/P: FULL LOAD Ta= -25℃	TEST: OK																																																																																				
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 45 °C NO DAMAGE	I/P: 305VAC O/P: FULL LOAD Ta=45 °C HUMIDITY= 95% R.H	TEST: OK																																																																																				
4	TEMPERATURE COEFFICIENT	±0.03%/°C (0~45℃)	I/P: 230 VAC O/P: FULL LOAD	±0.009%/°C (0~45℃)																																																																																				
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature: -45℃ ~ +90℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle: 5 CYCLE 5. Input/Output condition: STATIC		TEST: OK																																																																																				



25W PWM Output LED Driver

IDLV-25 series

6	THERMAL SHOCK TEST	1. Thermal shock Temperature: -25°C ~ +50°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle: 10 CYCLE 5. Input/Output condition: 230VAC/Full Load AC ON/OFF TEST AC on 3 sec/AC off 1 sec TEST	TEST: OK
7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency: 10-500Hz (3) Sweep Time: 10min/sweep cycle (4) Acceleration: 2G (5) Test Time: 180min in each axis (X.Y.Z) (6) Ta: 25°C	TEST: OK
8	CAPACITOR LIFE CYCLE	IDLV-25-36: SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P: 230VAC O/P: FULL LOAD Ta= 25 °C LIFE TIME (2) I/P: 230VAC O/P: FULL LOAD Ta= 45 °C LIFE TIME (3) I/P: 230VAC O/P: 75% LOAD Ta= 45 °C LIFE TIME (4) I/P: 230VAC O/P: 50% LOAD Ta= 45 °C LIFE TIME	(1) 214612 HRS (2) 65578 HRS (3) 70459 HRS (4) 84620 HRS
9	MTBF	Conducted by Parts Stress Analysis Prediction 382.7K hrs min MIL-HDBK-217F (25°C)	
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 30,000 hours @ Tcase 85°C	

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	CHENZH/ZHUOKB	SKY	LIUWY