



# Test Report: IDLV-45-48

---

45W PWM Output LED Driver

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

## ■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

## ■ RELIABILITY TEST

Environment Test



■ DESIGN VERIFY TEST


**OUTPUT FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM FREQUENCY	1KHz (±20%)	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	828Hz
2	VOLTAGE TOLERANCE	± 10%	I/P: 90 VAC / 295 VAC O/P: 70%/FULL/ NO LOAD Ta: 25°C	-0.675%~1.350%
3	OVER/UNDERSHOOT TEST	<±10 %	I/P: 230VAC O/P: FULL LOAD Ta: 25°C	<±10 %
4	SET UP TIME(Max)	500ms/230VAC 1200ms/115VAC	I/P: 230 VAC I/P: 115 VAC O/P: FULL /80%LOAD Ta: 25°C	350ms/230VAC 944ms/115VAC
<div style="display: flex; justify-content: space-around;"> <div style="width: 45%;"> <p>INPUT=230VAC/50HZ @ FULL LOAD</p> <p>CH1: Output Voltage CH2: AC Input Voltage</p> <p>Ch1 Max 1.27 A</p> </div> <div style="width: 45%;"> <p>INPUT=115VAC/60HZ @ FULL LOAD</p> <p>CH1: Output Voltage CH2: AC Input Voltage</p> <p>Ch1 Max 1.22 A</p> </div> </div>				
5	AUXILIARY DC OUTPUT (For A-Type only)	Nominal 12V (deviation 11.4~12.6) @50mA	I/P: 230 VAC O/P: FULL LOAD	11.90V

6 DIMMING TEST

※ Dimming principle for PWM style output

Dimming is achieved by varying the duty cycle of the output current.




$$\text{Duty cycle(\%)} = \frac{T_{ON}}{T} \times 100\%$$


Output PWM frequency : 1KHz(±20%)

※ 2 in 1 dimming function


◎ Applying additive 0 ~ 10VDC




"DO NOT connect "DIM- to Vo-"



◎ Applying additive 10V PWM signal (frequency range 300~3000Hz):



"DO NOT connect "DIM- to Vo-"



Note : 1. Min. duty cycle of output current is about 8% and the output current is not defined when 0% < Iout < 8%.  
 2. The duty cycle of output current could drop down to 0% when dimming input is about 0Vdc or 10V PWM signal with 0% duty cycle.

I/P: 230 VAC

O/P: DIMMING TEST

Ta: 25°C

1	Dimming voltage	0V	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	OPEN
	Output Current	0	0.09A	0.17A	0.26A	0.35A	0.44A	0.53A	0.63A	0.72A	0.81A	0.90A	0.91A
Duty cycle of output current	0%	9.5%	18.1%	27.7%	37.2%	46.8%	56.4%	67.0%	76.6%	86.2%	95.7%	96.8%	
2	Dimming Duty cycle	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	OPEN
	Output Current	0	0.08A	0.17A	0.29A	0.35A	0.44A	0.53A	0.63A	0.72A	0.81A	0.91A	0.91A
	Duty cycle of output current	0%	8.5%	18.1%	30.9%	37.2%	46.8%	56.4%	67.0%	76.6%	86.2%	96.8%	96.8%

TEST RESULT: OK




**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	90VAC~295VAC	I/P: TESTING O/P: FULL LOAD Ta: 25°C	87V~305V
			I/P: (1)LOW-LINE-3V=87 V HIGH-LINE+10V=305 V O/P: FULL/NO LOAD ON: 30 Sec OFF: 30 Sec 10MIN (2)230VAC ON: 0.5 Sec OFF: 0.5 Sec 20MIN ( POWER ON/OFF NO DAMAGE )	TEST: OK
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P: 90 VAC ~295 VAC O/P: FULL~NO LOAD Ta: 25°C	TEST: OK
3	AC CURRENT	0.6A/115VAC 0.4A/230VAC 0.3A/277VAC	I/P: 115 VAC I/P: 230 VAC I/P: 277 VAC O/P: 80%/FULL LOAD Ta: 25°C	I = 0.445A/ 115VAC I = 0.222A/ 230VAC I = 0.189A/ 277VAC
4	LEAKAGE CURRENT	< 0.75mA / 277VAC	I/P: 277 VAC O/P: NO LOAD Ta: 25°C	L-FG: 0.0027 mA N-FG: 0.0029 mA
5	NO LOAD POWER CONSUMPTION	< 0.5W for Blank-Type < 1.2W for A-Type	I/P: 230VAC O/P: NO LOAD Ta: 25°C	0.3877W for Blank-Type 0.3951W for A-Type
6	INRUSH CURRENT(Typ)	COLD START 30A/230VAC Twidth =150 us measured at 50% Ipeak	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	I=19.1 A/ 230VAC Twidth = 84.8us

INPUT=230VAC/50HZ @ FULL LOAD

CH2: Input current CH1: AC Input Voltage






45W PWM Output LED Driver

IDLV-45 series


7	POWER FACTOR	0.95/ 115VAC 0.92/ 230VAC 0.9/ 277VAC	I/P: 115 VAC I/P: 230 VAC I/P: 277 VAC O/P: 80%/FULL LOAD Ta: 25°C	PF=0.995 /115VAC PF=0.976 /230VAC PF=0.959 /277VAC
---	--------------	---	--	--

PF vs LOAD




8	TOTAL HARMONIC DISTORTION	THD < 20% (@load ≥ 60%/115VAC, 230VAC; @load ≥ 75%/277VAC)	I/P: 115 VAC I/P: 230 VAC I/P: 277 VAC O/P: 60%/75% LOAD Ta: 25°C	THD=6.20% @60% load /115VAC THD=8.55% @60% load /230VAC THD=10.76% @75% load /277VAC
---	---------------------------	--	---	--

THD vs LOAD



9	EFFICIENCY(Typ)	88%	I/P: 230VAC O/P: FULL LOAD Ta: 25°C	90.37%
---	-----------------	-----	---	--------

EFFICIENCY vs LOAD





## PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER CURRENT PROTECTION	105%~ 115%	I/P: 100VAC I/P: 230VAC I/P: 295VAC O/P: TESTING Ta: 25°C	113%/ 100VAC 112%/ 230VAC 113%/ 295VAC Hiccup mode, recovers automatically after fault condition is removed
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 90VAC I/P: 295VAC O/P: 70%/FULL LOAD Ta: 25°C	NO DAMAGE Shut down O/P voltage, re-power on to recovery

## COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated 9 A/800V	I/P: High-Line +3V =298V O/P: (1) Full Load Turn on (2) Output Short (3) Full load continue Ta: 25°C	(1) 666V (2) 616V (3) 628V
2	Diode Peak Voltage	D100 Rated 16A/400V	I/P: High-Line +3V =298V O/P: (1) Full Load Turn on (2) Output Short (3) Full load continue Ta: 25°C	(1) 326V (2) 328V (3) 320V
3	Control IC Voltage Test	U1 Rated 35V	I/P: High-Line +3V =298V O/P: (1) Full Load input on/off (2) NO load input on /Off (3) Full Load /NO load Change Ta: 25°C	(1) 14V (2) 13.7V (3) 13.9V



## SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P: 3.75KVAC/min	I/P-O/P: 4.2KVAC/min Ta: 25°C	I/P-O/P: 1.606mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P: 500VDC>100MΩ	I/P-O/P: 500VDC Ta: 25°C	I/P-O/P: 6193MΩ

## E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	EN61000-3-2 CLASS C	I/P: 230VAC/50HZ O/P: FULL /60% LOAD Ta: 25°C	PASS
2	CONDUCTION	EN55015	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
3	RADIATION	EN55015	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY Air: 8KV Contact: 4KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
6	SURGE	EN61000-4-5 LIGHT INDUSTRY L-N: 1KV	I/P: 230VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS
7	Test by certified Lab & Test Report Prepare			

■ **RELIABILITY TEST**

**ENVIRONMENT TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																																
1	TEMPERATURE RISE TEST	MODEL: IDLV-45-48 1. ROOM AMBIENT BURN-IN: 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 27.9°C 2. HIGH AMBIENT BURN-IN: 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 42.4°C																																																																		
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 27.9°C</th> <th>HIGH AMBIENT Ta=42.4°C</th> </tr> </thead> <tbody> <tr><td>1</td><td>L1</td><td>78.4°C</td><td>90.9°C</td></tr> <tr><td>2</td><td>BD1</td><td>76.1°C</td><td>88.4°C</td></tr> <tr><td>3</td><td>D1</td><td>84.9°C</td><td>97.5°C</td></tr> <tr><td>4</td><td>Q1</td><td>86.6°C</td><td>99.1°C</td></tr> <tr><td>5</td><td>U1</td><td>71.5°C</td><td>83.8°C</td></tr> <tr><td>6</td><td>T1</td><td>81.3°C</td><td>92.3°C</td></tr> <tr><td>7</td><td>C20</td><td>71.3°C</td><td>83.1°C</td></tr> <tr><td>8</td><td>D100</td><td>89.8°C</td><td>100.9°C</td></tr> <tr><td>9</td><td>C201</td><td>65.4°C</td><td>77.9°C</td></tr> <tr><td>10</td><td>Q100</td><td>55.2°C</td><td>68.2°C</td></tr> <tr><td>11</td><td>C6</td><td>65.3°C</td><td>78.5°C</td></tr> <tr><td>12</td><td>C105</td><td>59.9°C</td><td>72.7°C</td></tr> <tr><td>13</td><td>C107</td><td>50.5°C</td><td>63.7°C</td></tr> <tr><td>14</td><td>R18</td><td>88.4°C</td><td>99.8°C</td></tr> <tr><td>15</td><td>TC</td><td>64.5°C</td><td>76.5°C</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 27.9°C	HIGH AMBIENT Ta=42.4°C	1	L1	78.4°C	90.9°C	2	BD1	76.1°C	88.4°C	3	D1	84.9°C	97.5°C	4	Q1	86.6°C	99.1°C	5	U1	71.5°C	83.8°C	6	T1	81.3°C	92.3°C	7	C20	71.3°C	83.1°C	8	D100	89.8°C	100.9°C	9	C201	65.4°C	77.9°C	10	Q100	55.2°C	68.2°C	11	C6	65.3°C	78.5°C	12	C105	59.9°C	72.7°C	13	C107	50.5°C	63.7°C	14	R18	88.4°C	99.8°C	15	TC	64.5°C	76.5°C		
NO	Position	ROOM AMBIENT Ta= 27.9°C	HIGH AMBIENT Ta=42.4°C																																																																	
1	L1	78.4°C	90.9°C																																																																	
2	BD1	76.1°C	88.4°C																																																																	
3	D1	84.9°C	97.5°C																																																																	
4	Q1	86.6°C	99.1°C																																																																	
5	U1	71.5°C	83.8°C																																																																	
6	T1	81.3°C	92.3°C																																																																	
7	C20	71.3°C	83.1°C																																																																	
8	D100	89.8°C	100.9°C																																																																	
9	C201	65.4°C	77.9°C																																																																	
10	Q100	55.2°C	68.2°C																																																																	
11	C6	65.3°C	78.5°C																																																																	
12	C105	59.9°C	72.7°C																																																																	
13	C107	50.5°C	63.7°C																																																																	
14	R18	88.4°C	99.8°C																																																																	
15	TC	64.5°C	76.5°C																																																																	
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 295VAC/200VAC O/P: FULL LOAD Ta= -25°C	TEST: OK																																																																
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 40 °C NO DAMAGE	I/P: 305VAC O/P: FULL LOAD Ta=40 °C HUMIDITY= 95% R.H	TEST: OK																																																																
4	TEMPERATURE COEFFICIENT	±0.03%/°C (0~40°C)	I/P: 230 VAC O/P: FULL LOAD	±0.015%/°C (0~40°C)																																																																
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature: -45°C ~ +85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle: 5 CYCLE 5. Input/Output condition: STATIC		TEST: OK																																																																
6	THERMAL SHOCK TEST	1. Thermal shock Temperature: -25°C ~ +45°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle: 10 CYCLE 5. Input/Output condition: 230VAC/Full Load AC ON/OFF TEST AC on 3 sec/AC off 1 sec TEST		TEST: OK																																																																





45W PWM Output LED Driver

**IDLV-45 series**

7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency: 10~500Hz (3) Sweep Time: 10min/sweep cycle (4) Acceleration: 2G (5) Test Time: 60min in each axis (X.Y.Z) (6) Ta: 25°C	TEST: OK
8	CAPACITOR LIFE CYCLE	IDLV-45-48: SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P: 230VAC O/P: FULL LOAD Ta= 25 °C LIFE TIME (2) I/P: 230VAC O/P: FULL LOAD Ta= 40 °C LIFE TIME (3) I/P: 230VAC O/P: 75% LOAD Ta= 40 °C LIFE TIME (4) I/P: 230VAC O/P: 50% LOAD Ta= 40 °C LIFE TIME	(1) 410935 HRS (2) 163430 HRS (3) 213271 HRS (4) 274503 HRS
9	MTBF	Conducted by Parts Stress Analysis Prediction 4229.8K hrs min. Telcordia SR-332 (Bellcore) ; 434.9K hrs min. MIL-HDBK-217F (25°C)	
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 30,000 hours @ Tcase 85°C ; 50,000 hours @ Tcase 75°C	

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	CHENZH/ZHUOKB	SKY	LIUWY