



Test Report: ODLC-45-1400

45W Constant Current Mode LED Driver

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST


NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	CONSTANT CURRENT REGION	19V~32V	I/P: 230VAC O/P: LED MODE Ta: 25°C	17V~34V
2	CURRENT RIPPLE	5% max@rated current	I/P: 230VAC O/P: FULL/MIN LOAD Ta: 25°C	2.42%
3	CURRENT TOLERANCE	±7%	I/P: 230VAC O/P: FULL/MIN LOAD Ta: 25°C	±0.71%
4	OPEN CIRCUIT VOLTAGE (max)	50V	I/P: 230VAC O/P: NO LOAD Ta: 25°C	44.44V
5	OVER/UNDERSHOOT TEST	<±5 %	I/P: 230VAC O/P: FULL LOAD Ta: 25°C	<5 %
6	SET UP TIME	500ms/230VAC 1200ms/115VAC	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	430ms/230VAC 440ms/115VAC
<div style="display: flex; justify-content: space-around;"> <div style="width: 45%;"> <p>INPUT=230VAC/50HZ @ FULL LOAD</p> <p>CH1: Output Voltage CH2: AC Input Voltage</p> <p>Trig? Δ: 28.9 V @: 28.8 V Δ: 430ms @: 128ms</p> <p>Ch1 6.00 V Ch2 250 V M 100ms A Ch1 24.2 V</p> <p>50.00 %</p> </div> <div style="width: 45%;"> <p>INPUT=115VAC/60HZ @ FULL LOAD</p> <p>CH1: Output Voltage CH2: AC Input Voltage</p> <p>Δ: 15.0 V @: -2.00 V Δ: 440ms @: -278ms</p> <p>Ch1 6.00 V Ch2 100 V M 100ms A Ch1 25.6 V</p> <p>50.00 %</p> </div> </div>				
7	AUXILIARY DC OUTPUT (A-Type only)	Nominal 12V (deviation 11.4~12.6) @50mA	I/P: 230 VAC O/P: FULL LOAD	11.95 V

8 DIMMING TEST

SPEC:


- Output constant current level can be adjusted by applying one of the two methodologies between DIM+ and DIM-: 0 ~ 10Vdc, or 10V PWM signal.
- Direct connecting to LEDs is suggested. It is not suitable to be used with additional drivers.

◎ Applying additive 0 ~ 10VDC





"DO NOT connect "DIM- to Vo-"

◎ Applying additive 10V PWM signal (frequency range 300Hz ~ 3KHz):



"DO NOT connect "DIM- to Vo-"



- Note: 1. Min. dimming level is about 8% and the output current is not defined when 0% < I_{out} < 8%.
 2. The output current could drop down to 0% when dimming input is about 0Vdc or 10V PWM signal with 0% duty cycle.

I/P: 230 VAC

O/P: DIMMING TEST

Ta: 25°C

1	V	0V	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V
	Output Current	0A	0.138	0.290	0.424	0.563	0.699	0.840	0.980	1.110	1.250	1.388
%	0.00%	9.86%	20.71%	30.29%	40.21%	49.93%	60.00%	70.00%	79.29%	89.29%	99.14%	
2	PWM(100Hz)	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
	Output Current	0A	0.145	0.294	0.432	0.566	0.703	0.837	0.970	1.107	1.243	1.365
	%	0.00%	10.36%	21.00%	30.83%	40.44%	50.19%	59.79%	69.29%	79.07%	88.79%	97.50%


TEST RESULT: OK

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	90VAC~295VAC	I/P: TESTING O/P: FULL LOAD Ta: 25°C	87V~305V
			I/P: (1)LOW-LINE-3V=87 V HIGH-LINE+10V=305 V O/P: FULL/MIN LOAD ON: 30 Sec OFF: 30 Sec 10MIN (2)230VAC ON: 0.5 Sec OFF: 0.5 Sec 20MIN (POWER ON/OFF NO DAMAGE)	TEST: OK
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P: 90 VAC ~295 VAC O/P: FULL~MIN LOAD Ta: 25°C	TEST: OK
3	AC CURRENT	0.6A/115VAC 0.4A/230VAC 0.3A/277VAC	I/P: 115 VAC I/P: 230 VAC I/P: 277 VAC O/P: FULL LOAD Ta: 25°C	I =0.446A/ 115VAC I =0.225A/ 230VAC I =0.194A/ 277VAC
4	LEAKAGE CURRENT	< 0.75mA / 277VAC	I/P: 277 VAC O/P: NO LOAD Ta: 25°C	L-CASE: 0.0029 mA N-CASE: 0.0029 mA
5	NO LOAD POWER CONSUMPTION	< 0.5W for Blank-Type < 1.2W for A-Type	I/P: 230VAC O/P: NO LOAD Ta: 25°C	0.325W for Blank-Type 0.458W for A-Type
6	INRUSH CURRENT(Typ)	230V/ 30A Twidth =100 us measured at 50% Ipeak COLD START	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	I =22.5A/ 230VAC Twidth =80.8us

INPUT=230VAC/50HZ @ FULL LOAD

CH1: AC Input Voltage CH2: Input current



7	EFFICIENCY(Typ)	83%	I/P: 230VAC O/P: FULL LOAD Ta: 25°C	86.41%																												
<p>EFFICIENCY vs LOAD</p> <table border="1"> <caption>Efficiency vs Load Data</caption> <thead> <tr> <th>LOAD</th> <th>277V</th> <th>230V</th> <th>115V</th> </tr> </thead> <tbody> <tr> <td>50%</td> <td>78.0</td> <td>79.0</td> <td>79.0</td> </tr> <tr> <td>60%</td> <td>80.5</td> <td>81.5</td> <td>81.0</td> </tr> <tr> <td>70%</td> <td>82.5</td> <td>83.5</td> <td>82.5</td> </tr> <tr> <td>80%</td> <td>84.0</td> <td>84.5</td> <td>83.5</td> </tr> <tr> <td>90%</td> <td>85.5</td> <td>86.0</td> <td>84.5</td> </tr> <tr> <td>100%</td> <td>86.0</td> <td>86.5</td> <td>85.0</td> </tr> </tbody> </table>					LOAD	277V	230V	115V	50%	78.0	79.0	79.0	60%	80.5	81.5	81.0	70%	82.5	83.5	82.5	80%	84.0	84.5	83.5	90%	85.5	86.0	84.5	100%	86.0	86.5	85.0
LOAD	277V	230V	115V																													
50%	78.0	79.0	79.0																													
60%	80.5	81.5	81.0																													
70%	82.5	83.5	82.5																													
80%	84.0	84.5	83.5																													
90%	85.5	86.0	84.5																													
100%	86.0	86.5	85.0																													
8	POWER FACTOR	0.95/ 115VAC 0.92/ 230VAC 0.90/ 277VAC	I/P: 115 VAC I/P: 230 VAC I/P: 277 VAC O/P: FULL LOAD Ta: 25°C	PF=0.985/ 115VAC PF=0.980/ 230VAC PF=0.949/ 277VAC																												
<p>P.F vs LOAD</p> <table border="1"> <caption>P.F vs Load Data</caption> <thead> <tr> <th>LOAD</th> <th>277V</th> <th>230V</th> <th>115V</th> </tr> </thead> <tbody> <tr> <td>50%</td> <td>0.89</td> <td>0.95</td> <td>0.98</td> </tr> <tr> <td>60%</td> <td>0.90</td> <td>0.96</td> <td>0.98</td> </tr> <tr> <td>70%</td> <td>0.92</td> <td>0.97</td> <td>0.98</td> </tr> <tr> <td>80%</td> <td>0.93</td> <td>0.97</td> <td>0.98</td> </tr> <tr> <td>90%</td> <td>0.94</td> <td>0.97</td> <td>0.98</td> </tr> <tr> <td>100%</td> <td>0.95</td> <td>0.97</td> <td>0.97</td> </tr> </tbody> </table>					LOAD	277V	230V	115V	50%	0.89	0.95	0.98	60%	0.90	0.96	0.98	70%	0.92	0.97	0.98	80%	0.93	0.97	0.98	90%	0.94	0.97	0.98	100%	0.95	0.97	0.97
LOAD	277V	230V	115V																													
50%	0.89	0.95	0.98																													
60%	0.90	0.96	0.98																													
70%	0.92	0.97	0.98																													
80%	0.93	0.97	0.98																													
90%	0.94	0.97	0.98																													
100%	0.95	0.97	0.97																													
9	TOTAL HARMONIC DISTORTION	THD<20% (@load≥60%/115VAC, 230VAC; @load≥75%/277VAC)	I/P: 115 VAC/60% LOAD I/P: 230 VAC/60% LOAD I/P: 277 VAC/75% LOAD Ta: 25°C	THD=10.35% @60% load /115VAC THD=11.62% @60% load /230VAC THD=9.04% @75% load /277VAC																												
<p>THD vs LOAD</p> <table border="1"> <caption>THD vs Load Data</caption> <thead> <tr> <th>LOAD</th> <th>277V</th> <th>230V</th> <th>115V</th> </tr> </thead> <tbody> <tr> <td>50%</td> <td>11.5</td> <td>12.0</td> <td>11.5</td> </tr> <tr> <td>60%</td> <td>9.0</td> <td>11.5</td> <td>10.5</td> </tr> <tr> <td>70%</td> <td>9.0</td> <td>10.5</td> <td>10.0</td> </tr> <tr> <td>80%</td> <td>9.0</td> <td>10.0</td> <td>9.0</td> </tr> <tr> <td>90%</td> <td>9.5</td> <td>10.0</td> <td>8.5</td> </tr> <tr> <td>100%</td> <td>9.5</td> <td>9.5</td> <td>9.0</td> </tr> </tbody> </table>					LOAD	277V	230V	115V	50%	11.5	12.0	11.5	60%	9.0	11.5	10.5	70%	9.0	10.5	10.0	80%	9.0	10.0	9.0	90%	9.5	10.0	8.5	100%	9.5	9.5	9.0
LOAD	277V	230V	115V																													
50%	11.5	12.0	11.5																													
60%	9.0	11.5	10.5																													
70%	9.0	10.5	10.0																													
80%	9.0	10.0	9.0																													
90%	9.5	10.0	8.5																													
100%	9.5	9.5	9.0																													

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	SHORT CIRCUIT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 90VAC I/P: 295VAC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Hiccup mode, recovers automatically after fault condition is removed

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Power Transistor	Q 1 Rated 800V/9A	I/P: High-Line +3V =298V O/P: (1) Full Load Turn on (2) Output Short (3) Full load continue Ta: 25°C	(1) 758V (2) 752V (3) 720V
2	O/P Diode (MOSFET)	D100 Rated 400V/16A	I/P: High-Line +3V =298V O/P: (1) Full Load Turn on (2) Output Short (3) Full load continue Ta: 25°C	(1) 246V (2) 253V (3) 242V
3	Control IC	U1 Rated 35V (MAX)	I/P: High-Line +3V =298V O/P: (1) FULL LOAD (2) Output Short (3) Low Line No Load Ta: 25°C	(1) 15.0V (2) 14.6V (3) 14.5V
4	Clamp Diode	D 1 Rated 1000V/1A	I/P: High-Line +3V = 298V O/P: (1) Full Load input on/off (2) Output Short Ta: 25°C	(1) 494V (2) 484V

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P: 3.75KVAC/min	I/P-O/P: 4.2 KVAC/min Ta: 25°C	I/P-O/P: 1.630mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P: 500VDC>100MΩ	I/P-O/P: 500 VDC Ta: 25°C/70% RH	I/P-O/P: >9999MΩ

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	EN61000-3-2 CLASS C	I/P: 230 VAC/50HZ O/P: FULL/60% LOAD Ta: 25°C	PASS
2	CONDUCTION	EN55015	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab
3	RADIATION	EN55015	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR: 8KV Contact: 4KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA A
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA A
6	SURGE	EN61000-4-5 LIGHT INDUSTRY L-N: 1KV	I/P: 230VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA A
7	Test by certified Lab & Test Report Prepare			

■ **RELIABILITY TEST**

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																												
1	TEMPERATURE RISE TEST	MODEL: ODLIC-45-1400 1. ROOM AMBIENT BURN-IN: 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 32.5℃ 2. HIGH AMBIENT BURN-IN: 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 53.7℃																																																														
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 32.5 ℃</th> <th>HIGH AMBIENT Ta=53.7 ℃</th> </tr> </thead> <tbody> <tr><td>1</td><td>L1</td><td>66.1℃</td><td>89.1℃</td></tr> <tr><td>2</td><td>BD1</td><td>64.0℃</td><td>86.7℃</td></tr> <tr><td>3</td><td>Q1</td><td>69.3℃</td><td>92.1℃</td></tr> <tr><td>4</td><td>U1</td><td>64.5℃</td><td>87.0℃</td></tr> <tr><td>5</td><td>T1</td><td>68.4℃</td><td>87.8℃</td></tr> <tr><td>6</td><td>C16</td><td>62.3℃</td><td>85.1℃</td></tr> <tr><td>7</td><td>RG1</td><td>71.2℃</td><td>94.6℃</td></tr> <tr><td>8</td><td>D100</td><td>68.3℃</td><td>91.8℃</td></tr> <tr><td>9</td><td>C201</td><td>65.6℃</td><td>89.3℃</td></tr> <tr><td>10</td><td>Q100</td><td>65.1℃</td><td>89.1℃</td></tr> <tr><td>11</td><td>R138</td><td>68.3℃</td><td>91.9℃</td></tr> <tr><td>12</td><td>L100</td><td>63.4℃</td><td>87.4℃</td></tr> <tr><td>13</td><td>C105</td><td>62.0℃</td><td>85.5℃</td></tr> <tr><td>14</td><td>Tc</td><td>61.1℃</td><td>83.3℃</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 32.5 ℃	HIGH AMBIENT Ta=53.7 ℃	1	L1	66.1℃	89.1℃	2	BD1	64.0℃	86.7℃	3	Q1	69.3℃	92.1℃	4	U1	64.5℃	87.0℃	5	T1	68.4℃	87.8℃	6	C16	62.3℃	85.1℃	7	RG1	71.2℃	94.6℃	8	D100	68.3℃	91.8℃	9	C201	65.6℃	89.3℃	10	Q100	65.1℃	89.1℃	11	R138	68.3℃	91.9℃	12	L100	63.4℃	87.4℃	13	C105	62.0℃	85.5℃	14	Tc	61.1℃	83.3℃
NO	Position	ROOM AMBIENT Ta= 32.5 ℃	HIGH AMBIENT Ta=53.7 ℃																																																													
1	L1	66.1℃	89.1℃																																																													
2	BD1	64.0℃	86.7℃																																																													
3	Q1	69.3℃	92.1℃																																																													
4	U1	64.5℃	87.0℃																																																													
5	T1	68.4℃	87.8℃																																																													
6	C16	62.3℃	85.1℃																																																													
7	RG1	71.2℃	94.6℃																																																													
8	D100	68.3℃	91.8℃																																																													
9	C201	65.6℃	89.3℃																																																													
10	Q100	65.1℃	89.1℃																																																													
11	R138	68.3℃	91.9℃																																																													
12	L100	63.4℃	87.4℃																																																													
13	C105	62.0℃	85.5℃																																																													
14	Tc	61.1℃	83.3℃																																																													
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 295VAC/90VAC O/P: FULL/80% LOAD Ta= -25℃	TEST: OK																																																												
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 ℃ NO DAMAGE	I/P: 305VAC O/P: FULL LOAD Ta=50 ℃ HUMIDITY= 95 %R.H	TEST: OK																																																												
4	TEMPERATURE COEFFICIENT	±0.03 %/℃(0~40℃)	I/P: 230 VAC O/P: FULL LOAD	±0.001%/℃																																																												
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature: -45℃~ +85℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle: 5 CYCLE 5. Input/Output condition: AC OFF STATIC		TEST: OK																																																												



6	THERMAL SHOCK TEST	1. Thermal shock Temperature: Tcase=-25°C~ +85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle: 16 CYCLE 5. Input/Output condition: 230VAC/Full Load AC ON/OFF TEST AC on 3 sec/AC off 1 sec TEST	TEST: OK
7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency: 10~500Hz (3) Sweep Time: 10min/sweep cycle (4) Acceleration: 2G (5) Test Time: 60min in each axis (X.Y.Z) (6) Ta: 25°C	TEST: OK
8	CAPACITOR LIFE CYCLE	ODL-45-1400: SUPPOSE C106 IS THE MOST CRITICAL COMPONENT (1) I/P: 230VAC O/P: FULL LOAD Ta= 25 °C LIFE TIME (2) I/P: 230VAC O/P: FULL LOAD Ta= 50 °C LIFE TIME (3) I/P: 230VAC O/P: 75% LOAD Ta= 50 °C LIFE TIME (4) I/P: 230VAC O/P: MIN LOAD Ta= 50 °C LIFE TIME	(1) 661156 HRS (2) 116857 HRS (3) 133360 HRS (4) 152217 HRS
9	MTBF	Conducted by Parts Stress Analysis Prediction 408.8K hrs min. MIL-HDBK-217F (25°C)	
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 30,000 hours @ Tcase 85°C ; 50,000 hours @ Tcase 75°C	

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	Carychen/ZHUOKB	SKY	LIUWY