



Test Report: ODLC-45-350

45W Constant Current Mode LED Driver

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST


OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	CONSTANT CURRENT REGION	57V~95V	I/P: 230VAC O/P: LED MODE Ta: 25°C	50V~98V
2	CURRENT RIPPLE	5% max@rated current	I/P: 230VAC O/P: FULL/MIN LOAD Ta: 25°C	4.85%
3	CURRENT TOLERANCE	±7%	I/P: 230VAC O/P: FULL/MIN LOAD Ta: 25°C	±3.14%
4	OPEN CIRCUIT VOLTAGE (max)	118V	I/P: 230VAC O/P: NO LOAD Ta: 25°C	117.6V
5	OVER/UNDERSHOOT TEST	<±5 %	I/P: 230VAC O/P: FULL LOAD Ta: 25°C	<5 %
6	SET UP TIME	500ms/230VAC 1200ms/115VAC	I/P: 230 VAC I/P: 115 VAC O/P: FULL LOAD Ta: 25°C	306ms/230VAC 482ms/115VAC
<div style="display: flex; justify-content: space-around;"> <div style="width: 45%;"> <p>INPUT=230VAC/50HZ @ FULL LOAD</p> <p>CH1: Output Voltage CH2: AC Input Voltage</p> <p>Ch1 19.0 V Ch2 250 V M 100ms A Ch1 76.0 V</p> <p>50.00 %</p> </div> <div style="width: 45%;"> <p>INPUT=115VAC/60HZ @ FULL LOAD</p> <p>CH1: Output Voltage CH2: AC Input Voltage</p> <p>Ch1 19.0 V Ch2 100 V M 100ms A Ch1 76.0 V</p> <p>50.00 %</p> </div> </div>				
7	AUXILIARY DC OUTPUT (For A-Type only)	Nominal 12V (deviation 11.4~12.6) @50mA	I/P: 230 VAC O/P: FULL LOAD	11.97 V

8 DIMMING TEST


SPEC:

- Output constant current level can be adjusted by applying one of the two methodologies between DIM+ and DIM-:
0 ~ 10Vdc, or 10V PWM signal.
 - Direct connecting to LEDs is suggested. It is not suitable to be used with additional drivers.
- © Applying additive 0 ~ 10VDC





"DO NOT connect "DIM- to Vo-"

- © Applying additive 10V PWM signal (frequency range 300Hz ~ 3KHz):



"DO NOT connect "DIM- to Vo-"



- Note : 1. Min. dimming level is about 8% and the output current is not defined when $0\% < I_{out} < 8\%$.
2. The output current could drop down to 0% when dimming input is about 0Vdc or 10V PWM signal with 0% duty cycle.

I/P: 230 VAC

O/P: DIMMING TEST

Ta: 25°C

	v	0V	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V
1	Output Current	0A	0.040	0.074	0.109	0.144	0.179	0.215	0.250	0.284	0.319	0.353
	%	0.00%	11.43%	21.14%	31.09%	41.03%	51.09%	61.29%	71.40%	81.20%	91.14%	100.86%
2	PWM(100Hz)	0%	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%
	Output Current	0A	0.038	0.070	0.108	0.143	0.177	0.212	0.246	0.281	0.316	0.347
	%	0.00%	10.83%	20.00%	30.86%	40.74%	50.66%	60.46%	70.37%	80.31%	90.17%	99.09%


TEST RESULT: OK

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	90VAC~295VAC	I/P: TESTING O/P: FULL LOAD Ta: 25°C	87V~305V
			I/P: (1)LOW-LINE-3V=87 V HIGH-LINE+10V=305 V O/P: FULL/MIN LOAD ON: 30 Sec OFF: 30 Sec 10MIN (2)230VAC ON: 0.5 Sec OFF: 0.5 Sec 20MIN (POWER ON/OFF NO DAMAGE)	TEST: OK
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P: 90 VAC ~295 VAC O/P: FULL~MIN LOAD Ta: 25°C	TEST: OK
3	AC CURRENT	0.6A/115VAC 0.4A/230VAC 0.3A/277VAC	I/P: 115 VAC I/P: 230 VAC I/P: 277 VAC O/P: FULL LOAD Ta: 25°C	I =0.337A/ 115VAC I =0.171A/ 230VAC I =0.151A/ 277VAC
4	LEAKAGE CURRENT	< 0.75mA / 277VAC	I/P: 277 VAC O/P: NO LOAD Ta: 25°C	L-CASE: 0.0029 mA N-CASE: 0.0029 mA
5	NO LOAD POWER CONSUMPTION	< 0.5W for Blank-Type < 1.2W for A-Type	I/P: 230VAC O/P: NO LOAD Ta: 25°C	0.368W for Blank-Type 0.585W for A-Type
6	INRUSH CURRENT(Typ)	230V/ 30A Twidth =100 us measured at 50% Ipeak COLD START	I/P: 230 VAC O/P: FULL LOAD Ta: 25°C	I =21.2A/ 230VAC Twidth =79.2us

INPUT=230VAC/50HZ @ FULL LOAD

CH1: AC Input Voltage CH2: Input current



7	EFFICIENCY(Typ)	86%	I/P: 230VAC O/P: FULL LOAD Ta: 25°C	89.18%																												
<p>EFFICIENCY vs LOAD</p> <table border="1"> <caption>Efficiency vs Load Data</caption> <thead> <tr> <th>LOAD</th> <th>277V</th> <th>230V</th> <th>115V</th> </tr> </thead> <tbody> <tr><td>50%</td><td>80.0</td><td>81.5</td><td>84.0</td></tr> <tr><td>60%</td><td>82.5</td><td>84.0</td><td>86.0</td></tr> <tr><td>70%</td><td>84.5</td><td>86.0</td><td>87.5</td></tr> <tr><td>80%</td><td>86.5</td><td>87.5</td><td>88.5</td></tr> <tr><td>90%</td><td>88.0</td><td>88.5</td><td>89.0</td></tr> <tr><td>100%</td><td>88.5</td><td>89.0</td><td>89.5</td></tr> </tbody> </table>					LOAD	277V	230V	115V	50%	80.0	81.5	84.0	60%	82.5	84.0	86.0	70%	84.5	86.0	87.5	80%	86.5	87.5	88.5	90%	88.0	88.5	89.0	100%	88.5	89.0	89.5
LOAD	277V	230V	115V																													
50%	80.0	81.5	84.0																													
60%	82.5	84.0	86.0																													
70%	84.5	86.0	87.5																													
80%	86.5	87.5	88.5																													
90%	88.0	88.5	89.0																													
100%	88.5	89.0	89.5																													
8	POWER FACTOR	0.95/ 115VAC 0.92/ 230VAC 0.90/ 277VAC	I/P: 115 VAC I/P: 230 VAC I/P: 277 VAC O/P: FULL LOAD Ta: 25°C	PF=0.996/ 115VAC PF=0.974/ 230VAC PF=0.938/ 277VAC																												
<p>P.F vs LOAD</p> <table border="1"> <caption>P.F vs Load Data</caption> <thead> <tr> <th>LOAD</th> <th>277V</th> <th>230V</th> <th>115V</th> </tr> </thead> <tbody> <tr><td>50%</td><td>0.85</td><td>0.94</td><td>0.99</td></tr> <tr><td>60%</td><td>0.88</td><td>0.95</td><td>0.99</td></tr> <tr><td>70%</td><td>0.90</td><td>0.96</td><td>0.99</td></tr> <tr><td>80%</td><td>0.92</td><td>0.97</td><td>0.99</td></tr> <tr><td>90%</td><td>0.93</td><td>0.97</td><td>0.99</td></tr> <tr><td>100%</td><td>0.94</td><td>0.98</td><td>0.99</td></tr> </tbody> </table>					LOAD	277V	230V	115V	50%	0.85	0.94	0.99	60%	0.88	0.95	0.99	70%	0.90	0.96	0.99	80%	0.92	0.97	0.99	90%	0.93	0.97	0.99	100%	0.94	0.98	0.99
LOAD	277V	230V	115V																													
50%	0.85	0.94	0.99																													
60%	0.88	0.95	0.99																													
70%	0.90	0.96	0.99																													
80%	0.92	0.97	0.99																													
90%	0.93	0.97	0.99																													
100%	0.94	0.98	0.99																													
9	TOTAL HARMONIC DISTORTION	THD<20% (@load≥60%/115VAC, 230VAC; @load≥75%/277VAC)	I/P: 115 VAC/60% LOAD I/P: 230 VAC/60% LOAD I/P: 277 VAC/75% LOAD Ta: 25°C	THD=6.72% @60% load /115VAC THD=8.30% @60% load /230VAC THD=9.92% @75% load /277VAC																												
<p>THD vs LOAD</p> <table border="1"> <caption>THD vs Load Data</caption> <thead> <tr> <th>LOAD</th> <th>277V</th> <th>230V</th> <th>115V</th> </tr> </thead> <tbody> <tr><td>50%</td><td>9.5</td><td>8.0</td><td>6.0</td></tr> <tr><td>60%</td><td>9.5</td><td>8.3</td><td>6.7</td></tr> <tr><td>70%</td><td>9.8</td><td>8.8</td><td>6.8</td></tr> <tr><td>80%</td><td>10.0</td><td>9.2</td><td>6.5</td></tr> <tr><td>90%</td><td>10.5</td><td>9.8</td><td>6.6</td></tr> <tr><td>100%</td><td>11.0</td><td>10.0</td><td>6.7</td></tr> </tbody> </table>					LOAD	277V	230V	115V	50%	9.5	8.0	6.0	60%	9.5	8.3	6.7	70%	9.8	8.8	6.8	80%	10.0	9.2	6.5	90%	10.5	9.8	6.6	100%	11.0	10.0	6.7
LOAD	277V	230V	115V																													
50%	9.5	8.0	6.0																													
60%	9.5	8.3	6.7																													
70%	9.8	8.8	6.8																													
80%	10.0	9.2	6.5																													
90%	10.5	9.8	6.6																													
100%	11.0	10.0	6.7																													

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	SHORT CIRCUIT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 90VAC I/P: 295VAC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Hiccup mode, recovers automatically after fault condition is removed

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Power Transistor	Q 1 Rated 800V/6A	I/P: High-Line +3V =298V O/P: (1) Full Load Turn on (2) Output Short (3) Full load continue Ta: 25°C	(1) 602V (2) 614V (3) 550V
2	O/P Diode (MOSFET)	D101 Rated 1000V/5A	I/P: High-Line +3V =298V O/P: (1) Full Load Turn on (2) Output Short (3) Full load continue Ta: 25°C	(1) 860V (2) 868V (3) 804V
3	Control IC	U1 Rated 35V (MAX)	I/P: High-Line +3V =298V O/P: (1) FULL LOAD (2) Output Short (3) Low Line No Load Ta: 25°C	(1) 15.1V (2) 14.7V (3) 15.0V
4	Clamp Diode	D 1 Rated 1000V/1A	I/P: High-Line +3V = 298V O/P: (1) Full Load input on/off (2) Output Short Ta: 25°C	(1) 530V (2) 484V

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P: 3.75KVAC/min	I/P-O/P: 4.2 KVAC/min Ta: 25°C	I/P-O/P: 1.624mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P: 500VDC>100MΩ	I/P-O/P: 500 VDC Ta: 25°C/70% RH	I/P-O/P: >9999MΩ

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	EN61000-3-2 CLASS C	I/P: 230 VAC/50HZ O/P: FULL/60% LOAD Ta: 25°C	PASS
2	CONDUCTION	EN55015	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab
3	RADIATION	EN55015	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR: 8KV Contact: 4KV	I/P: 230 VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA A
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA A
6	SURGE	EN61000-4-5 LIGHT INDUSTRY L-N: 1KV	I/P: 230VAC/50HZ O/P: FULL LOAD Ta: 25°C	CRITERIA A
7	Test by certified Lab & Test Report Prepare			

■ **RELIABILITY TEST**

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																												
1	TEMPERATURE RISE TEST	MODEL: ODL-45-700 1. ROOM AMBIENT BURN-IN: 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 32.5℃ 2. HIGH AMBIENT BURN-IN: 2 HRS I/P: 230VAC O/P: FULL LOAD Ta= 53.7℃																																																														
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 32.5 ℃</th> <th>HIGH AMBIENT Ta=53.7 ℃</th> </tr> </thead> <tbody> <tr><td>1</td><td>L1</td><td>69.7℃</td><td>91.0℃</td></tr> <tr><td>2</td><td>BD1</td><td>66.5℃</td><td>87.2℃</td></tr> <tr><td>3</td><td>D1</td><td>68.5℃</td><td>90.2℃</td></tr> <tr><td>4</td><td>Q1</td><td>72.1℃</td><td>93.8℃</td></tr> <tr><td>5</td><td>U1</td><td>66.2℃</td><td>87.1℃</td></tr> <tr><td>6</td><td>T1</td><td>71.1℃</td><td>92.3℃</td></tr> <tr><td>7</td><td>C16</td><td>65.5℃</td><td>86.7℃</td></tr> <tr><td>8</td><td>D101</td><td>73.3℃</td><td>94.1℃</td></tr> <tr><td>9</td><td>C201</td><td>63.5℃</td><td>84.5℃</td></tr> <tr><td>10</td><td>Q100</td><td>62.4℃</td><td>83.6℃</td></tr> <tr><td>11</td><td>L100</td><td>61.1℃</td><td>82.7℃</td></tr> <tr><td>12</td><td>C106</td><td>59.9℃</td><td>80.9℃</td></tr> <tr><td>13</td><td>C110</td><td>59.4℃</td><td>80.6℃</td></tr> <tr><td>14</td><td>Tc</td><td>60.9℃</td><td>80.3℃</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 32.5 ℃	HIGH AMBIENT Ta=53.7 ℃	1	L1	69.7℃	91.0℃	2	BD1	66.5℃	87.2℃	3	D1	68.5℃	90.2℃	4	Q1	72.1℃	93.8℃	5	U1	66.2℃	87.1℃	6	T1	71.1℃	92.3℃	7	C16	65.5℃	86.7℃	8	D101	73.3℃	94.1℃	9	C201	63.5℃	84.5℃	10	Q100	62.4℃	83.6℃	11	L100	61.1℃	82.7℃	12	C106	59.9℃	80.9℃	13	C110	59.4℃	80.6℃	14	Tc	60.9℃	80.3℃		
NO	Position	ROOM AMBIENT Ta= 32.5 ℃	HIGH AMBIENT Ta=53.7 ℃																																																													
1	L1	69.7℃	91.0℃																																																													
2	BD1	66.5℃	87.2℃																																																													
3	D1	68.5℃	90.2℃																																																													
4	Q1	72.1℃	93.8℃																																																													
5	U1	66.2℃	87.1℃																																																													
6	T1	71.1℃	92.3℃																																																													
7	C16	65.5℃	86.7℃																																																													
8	D101	73.3℃	94.1℃																																																													
9	C201	63.5℃	84.5℃																																																													
10	Q100	62.4℃	83.6℃																																																													
11	L100	61.1℃	82.7℃																																																													
12	C106	59.9℃	80.9℃																																																													
13	C110	59.4℃	80.6℃																																																													
14	Tc	60.9℃	80.3℃																																																													
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 295VAC/90VAC O/P: FULL/80% LOAD Ta= -25℃	TEST: OK																																																												
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 ℃ NO DAMAGE	I/P: 305VAC O/P: FULL LOAD Ta=50 ℃ HUMIDITY= 95 %R.H	TEST: OK																																																												
4	TEMPERATURE COEFFICIENT	±0.03 %/℃(0~40℃)	I/P: 230 VAC O/P: FULL LOAD	±0.001%/℃																																																												
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature: -45℃~ +85℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle: 5 CYCLE 5. Input/Output condition: AC OFF STATIC		TEST: OK																																																												



6	THERMAL SHOCK TEST	1. Thermal shock Temperature: Tcase=-25℃~ +85℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle: 16 CYCLE 5. Input/Output condition: 230VAC/Full Load AC ON/OFF TEST AC on 3 sec/AC off 1 sec TEST	TEST: OK
7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency: 10~500Hz (3) Sweep Time: 10min/sweep cycle (4) Acceleration: 2G (5) Test Time: 60min in each axis (X.Y.Z) (6) Ta: 25℃	TEST: OK
8	CAPACITOR LIFE CYCLE	ODL-45-700: SUPPOSE C106 IS THE MOST CRITICAL COMPONENT (1) I/P: 230VAC O/P: FULL LOAD Ta= 25 °C LIFE TIME (2) I/P: 230VAC O/P: FULL LOAD Ta= 50 °C LIFE TIME (3) I/P: 230VAC O/P: 75% LOAD Ta= 50 °C LIFE TIME (4) I/P: 230VAC O/P: MIN LOAD Ta= 50 °C LIFE TIME	(1) 555640 HRS (2) 84189 HRS (3) 99615 HRS (4) 107091 HRS
9	MTBF	Conducted by Parts Stress Analysis Prediction 408.8K hrs min. MIL-HDBK-217F (25℃)	
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 30,000 hours @ Tcase 85℃ ; 50,000 hours @ Tcase 75℃	

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	Carychen/ZHUOKB	SKY	LIUWY