



# Test Report: PCD-16-350B

---

16W Single Output AC Dimmable LED Power Supply

## ■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

## ■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

## ■ RELIABILITY TEST

ENVIRONMENT TEST

**DESIGN VERIFY TEST**
**OUTPUT FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 4.6 Vp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 1.34 Vp-p (Max)	P
2	SET UP TIME	230VAC : 500 ms (Max)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 377.542 ms	P
3	OPERATING VOLTAGE RANGE	24V~48V	I/P : 230VAC O/P : CV MODE Ta : 25°C	O/P= 24V : 0.36 A O/P= 47V : 0.36 A	P
4	OVER/UNDERSHOOT TEST	< 63V	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : < 63 V	P

**INPUT FUNCTION TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	180VAC~295 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	138 V~295V	P
			I/P : LOW-LINE-3V= 177 V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN ( AC POWER ON/OFF NO DAMAGE )	TEST : OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 180 VAC ~ 295 VAC O/P : FULL -MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.9 / 230 VAC(TYP)	I/P : 230 VAC (FULL LOAD) I/P : 277 VAC (FULL LOAD) O/P : FULL LOAD Ta : 25°C	PF= 0.971 / 230 VAC	P
		0.9 / 277 VAC(TYP)		PF= 0.91 / 277 VAC	
4	EFFICIENCY	82 % (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	82.68 %	P
5	INPUT CURRENT	230V/ 0.2 A (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I = 0.09 A/ 230 VAC	P
6	INRUSH CURRENT	230V/ 10 A (TYP) COLD START	I/P : 230 VAC  O/P : FULL LOAD Ta : 25°C	I = 7 A/ 230 VAC	P
7	LEAKAGE CURRENT	< 0.5 mA/ 240 VAC	I/P : 240 VAC O/P : Min LOAD Ta : 25°C	L-CASE : 0.01 mA N-CASE : 0.01 mA	P

## PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	95 % - 110 %	I/P : 230 VAC I/P : 180 VAC O/P : TESTING Ta : 25°C	105 %/ 230 VAC 105 %/ 180 VAC Constant Current Limiting recovers automatically after fault condition is removed.	P
2	OVER TEMPERATURE PROTECTION	SPEC : RTH1 : 95 ± 10°C O.T.P. Detect on heatsink of power transistor	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage · Re-power ON to recover	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 295 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE	P

## COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor ( D to S ) or ( C to E ) Peak Voltage	Q 1 Rated : STD4NK80ZT4 3A/800V	I/P : High-Line +3V = 298 V O/P : (1) Full Load Turn on (2) Output Short (3) Full load continue Ta : 25°C	(1) 560 V (2) 464 V (3) 540 V	P
2	Diode Peak Voltage	D100 Rated : NSF03A40 3A/400V	I/P : High-Line +3V = 298 V O/P : (1) Full Load Turn on (2) Output Short (3) Full load continue Ta : 25°C	(1) 338 V (2) 334 V (3) 310 V	P
3	Clamp Diode Peak Voltage	D 6 Rated : 1A/1KV 1N4007GP	I/P : High-Line +3V = 298 V O/P : (1) Full Load Turn on (2) Output Short (3) Full load continue Ta : 25°C	(1) 580 V (2) 440 V (3) 576 V	P
4	Control IC Voltage Test	U 1 Rated : PWM NCP1608B 10.2V~20V	I/P : High-Line +3V = 298 V O/P : (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta : 25°C	(1) 13.853 V (2) 13.675 V (3) 13.576 V	P

**SAFETY & E.M.C. TEST**
**SAFETY TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.75 KVAC/min	I/P-O/P : 4 KVAC/min Ta : 25°C	I/P-O/P : 1.17 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ	I/P-O/P : 500 VDC Ta : 25°C/70%RH	I/P-O/P : 30 GΩ NO DAMAGE	P
3	APPROVAL	TUV : Certificate NO : UL : File NO :			N/A

**E.M.C TEST**

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS C	I/P:230 /240//220VAC/50HZ LOAD:LED/ELECTRONIC LOAD O/P:40V/58VLOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55015 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55015 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																															
1	TEMPERATURE RISE TEST	MODEL : PCD-16-1400B 1. ROOM AMBIENT BURN-IN : 1 HRS I/P : 230VAC O/P : FULL LOAD Ta=30.3°C 2. HIGH AMBIENT BURN-IN : 3.5 HRS I/P : 230VAC O/P : FULL LOAD Ta=50°C			P																																																																																															
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 30.3 °C</th> <th>HIGH AMBIENT Ta= 50 °C</th> </tr> </thead> <tbody> <tr><td>6</td><td>LF1</td><td>LF804</td><td>61.3°C</td><td>75.4°C</td></tr> <tr><td>7</td><td>L1</td><td>TF2170</td><td>62.2°C</td><td>76.1°C</td></tr> <tr><td>8</td><td>BD1</td><td>2A/800V GLASS KBP208G</td><td>64.3°C</td><td>78.2°C</td></tr> <tr><td>9</td><td>C9</td><td>333/630V 10% P=7.5 MEX</td><td>59.1°C</td><td>73.4°C</td></tr> <tr><td>10</td><td>R1</td><td>3W 22KΩ 5% MINI</td><td>87.3°C</td><td>101.4°C</td></tr> <tr><td>11</td><td>R5</td><td>3W 330Ω 5% MINI</td><td>64.5°C</td><td>78.4°C</td></tr> <tr><td>12</td><td>C1</td><td>104/275VAC 20% P=10 R.46</td><td>69.1°C</td><td>82.6°C</td></tr> <tr><td>13</td><td>D30</td><td>HER204 2A/300V</td><td>66.2°C</td><td>80.3°C</td></tr> <tr><td>14</td><td>C48</td><td>22u/50V UL10Kh 5*11 YXM</td><td>66.1°C</td><td>80.1°C</td></tr> <tr><td>15</td><td>TSW1</td><td>220KΩ 3Φ TTC3A224F4371EY 1%</td><td>62.2°C</td><td>77.0°C</td></tr> <tr><td>16</td><td>T1</td><td>TF2146</td><td>73.1°C</td><td>87.0°C</td></tr> <tr><td>17</td><td>U1</td><td>NCP1608B</td><td>65.2°C</td><td>79.3°C</td></tr> <tr><td>18</td><td>Q1</td><td>STD4NK80ZT4 3A/800V DPAK</td><td>70.4°C</td><td>84.7°C</td></tr> <tr><td>19</td><td>C7</td><td>333/450V 10% P=7.5 MEC</td><td>68.1°C</td><td>81.9°C</td></tr> <tr><td>20</td><td>D100</td><td>B5100C 5A/100V SMC</td><td>77.0°C</td><td>90.7°C</td></tr> <tr><td>21</td><td>C105</td><td>2200u/16V UL10Kh 12.5*20 ZLH</td><td>62.0°C</td><td>76.5°C</td></tr> <tr><td>22</td><td>C54</td><td>33u/50V UL10Kh 6.3*11 YXM</td><td>63.0°C</td><td>77.1°C</td></tr> <tr><td>23</td><td>LF100</td><td>TR574-R2</td><td>57.4°C</td><td>72.6°C</td></tr> </tbody> </table>				NO	Position	P/N	ROOM AMBIENT Ta= 30.3 °C	HIGH AMBIENT Ta= 50 °C	6	LF1	LF804	61.3°C	75.4°C	7	L1	TF2170	62.2°C	76.1°C	8	BD1	2A/800V GLASS KBP208G	64.3°C	78.2°C	9	C9	333/630V 10% P=7.5 MEX	59.1°C	73.4°C	10	R1	3W 22KΩ 5% MINI	87.3°C	101.4°C	11	R5	3W 330Ω 5% MINI	64.5°C	78.4°C	12	C1	104/275VAC 20% P=10 R.46	69.1°C	82.6°C	13	D30	HER204 2A/300V	66.2°C	80.3°C	14	C48	22u/50V UL10Kh 5*11 YXM	66.1°C	80.1°C	15	TSW1	220KΩ 3Φ TTC3A224F4371EY 1%	62.2°C	77.0°C	16	T1	TF2146	73.1°C	87.0°C	17	U1	NCP1608B	65.2°C	79.3°C	18	Q1	STD4NK80ZT4 3A/800V DPAK	70.4°C	84.7°C	19	C7	333/450V 10% P=7.5 MEC	68.1°C	81.9°C	20	D100	B5100C 5A/100V SMC	77.0°C	90.7°C	21	C105	2200u/16V UL10Kh 12.5*20 ZLH	62.0°C	76.5°C	22	C54	33u/50V UL10Kh 6.3*11 YXM	63.0°C	77.1°C	23	LF100	TR574-R2	57.4°C	72.6°C
NO	Position	P/N	ROOM AMBIENT Ta= 30.3 °C	HIGH AMBIENT Ta= 50 °C																																																																																																
6	LF1	LF804	61.3°C	75.4°C																																																																																																
7	L1	TF2170	62.2°C	76.1°C																																																																																																
8	BD1	2A/800V GLASS KBP208G	64.3°C	78.2°C																																																																																																
9	C9	333/630V 10% P=7.5 MEX	59.1°C	73.4°C																																																																																																
10	R1	3W 22KΩ 5% MINI	87.3°C	101.4°C																																																																																																
11	R5	3W 330Ω 5% MINI	64.5°C	78.4°C																																																																																																
12	C1	104/275VAC 20% P=10 R.46	69.1°C	82.6°C																																																																																																
13	D30	HER204 2A/300V	66.2°C	80.3°C																																																																																																
14	C48	22u/50V UL10Kh 5*11 YXM	66.1°C	80.1°C																																																																																																
15	TSW1	220KΩ 3Φ TTC3A224F4371EY 1%	62.2°C	77.0°C																																																																																																
16	T1	TF2146	73.1°C	87.0°C																																																																																																
17	U1	NCP1608B	65.2°C	79.3°C																																																																																																
18	Q1	STD4NK80ZT4 3A/800V DPAK	70.4°C	84.7°C																																																																																																
19	C7	333/450V 10% P=7.5 MEC	68.1°C	81.9°C																																																																																																
20	D100	B5100C 5A/100V SMC	77.0°C	90.7°C																																																																																																
21	C105	2200u/16V UL10Kh 12.5*20 ZLH	62.0°C	76.5°C																																																																																																
22	C54	33u/50V UL10Kh 6.3*11 YXM	63.0°C	77.1°C																																																																																																
23	LF100	TR574-R2	57.4°C	72.6°C																																																																																																
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 230VAC/100VAC O/P : 100 % LOAD Ta= -30 °C	TEST : OK		P																																																																																														
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P : 295 VAC O/P : FULL LOAD Ta= 50 °C HUMIDITY= 95 %R.H	TEST : OK		P																																																																																														
4	TEMPERATURE COEFFICIENT	± 0.03 %(0-50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.005 %(0-50°C)		P																																																																																														
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																																																															
6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -30°C~ +50°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec		OK	P																																																																																															

7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10-500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 2G (5) Test Time : 72min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK	P
8	CAPACITOR LIFE CYCLE	PCD-16-1400B:SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta= 50 °C LIFE TIME	(1) 347252 HRS (2) 88034 HRS	P
9	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE : 906.5 HRS		P
10	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 30,000 hours @ Tcase 75°C ; 50,000 hours @ Tcase 65°C		P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2010/10/6	RD SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2010/11/10	PRODUCT SAMPLE	PASS	SANFORD SU	VINCENT TSENG

2009/08/04 A50-F023