

# 600W with PFC and Parallel Function



- Universal AC input / Full range
- PF>0.99@115VAC; >0.95@230VAC
- Protections: Short circuit / Overload / Over voltage / Over temp.
- Forced air cooling by built-in DC fan
- Built-in remote sense and ON/OFF control
- With DC OK signal output
- Current sharing up to 2400W (3+1)
- 3 years warranty

CASE: 910A

170x 120x 93 mm

AC input voltage range	88~264VAC; 124~370VDC
AC inrush current	Cold start, 20A at 115VAC, 40A at 230VAC
DC adjustment range	±10% rated output voltage
Overload protection	105%~135% constant current, auto-recovery
Over voltage protection	115%~140% rated output voltage
Withstand voltage	I/P-O/P:3kVAC, I/P-FG:1.5kVAC, 1 minute
Working temperature	-20~60°C (refer to output derating curve)
Safety standards	UL60950-1, TUV EN60950-1 approved
EMC standards	EN55022 class B, EN61000-3-2,3 EN61000-4-2,3,4,5,6,8,11, ENV50204
Connection	7+8P/ 9.5mm pitch terminal block with cover
Packing	1.9kg ; 8pcs / 15.5kg / 1.06CUFT

Model No.	Output	Tol.	R&N	Effi.
PSP-600-5	5V, 0~80.0A	±2%	180mV	79%
PSP-600-12	12V, 0~50.0A	±1%	240mV	84%
PSP-600-13.5	13.5V, 0~44.5A	±1%	240mV	85%
PSP-600-15	15V, 0~40.0A	±1%	240mV	85%
PSP-600-24	24V, 0~25.0A	±1%	240mV	86%
PSP-600-27	27V, 0~22.2A	±1%	240mV	86%
PSP-600-48	48V, 0~12.5A	±1%	300mV	87%