



Test Report: RSD-200C-12

200W Single Output DC-DC Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 120 mVp-p (Max)	I/P : 48VDC O/P : FULL LOAD Ta : 25°C	V1 : 7.8 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1 : 2%~ -2% (Max)	I/P : 28.8 VDC / 67.2VDC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.11 %~ -0.11 %	P
3	LINE REGULATION	V1 : 0.2%~ -0.2% (Max)	I/P : 28.8VDC ~ 67.2VDC O/P : FULL LOAD Ta : 25°C	V1 : 0 %~ 0 %	P
4	LOAD REGULATION	V1 : 1%~ -1% (Max)	I/P : 48VDC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 0.1 %~ -0.1 %	P
5	SET UP TIME	48VDC : 800 ms (Max)	I/P : 48VDC O/P : FULL LOAD Ta : 25°C	48VDC/ 26 ms	P
6	RISE TIME	48VDC : 50 ms (Max)	I/P : 48VDC O/P : FULL LOAD Ta : 25°C	48VDC/ 7 ms	P
7	HOLD UP TIME	48VDC : 3 ms (TYP)	I/P : 48VDC O/P : FULL LOAD Ta : 25°C	48VDC/ 6.4 ms	P
8	OVER/UNDERSHOOT TEST	< ±5%	I/P : 48VDC O/P : FULL LOAD Ta : 25°C	TEST : <5 %	P
9	DYNAMIC LOAD	V1 : 1200 mVp-p	I/P : 48VDC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1) 360 mVp-p (2) 576 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	28.8VDC~67.2VDC	I/P : TESTING O/P : FULL LOAD Ta : 25°C I/P : LOW-LINE=28.6V HIGH-LINE=70.2V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (DC POWER ON/OFF NO DAMAGE)	25.4 VDC~67.2VDC TEST : OK	P
2	EFFICIENCY	91 % (TYP)	I/P : 48VDC O/P : FULL LOAD Ta : 25°C	92.98 %	P
3	INPUT CURRENT	48VDC/ 4.8 A (TYP)	I/P : 48VDC O/P : FULL LOAD Ta : 25°C	I = 4.5 A/ 48VDC	P
4	INRUSH CURRENT	48VDC/ 45 A (TYP) COLD START	I/P : 48VDC O/P : FULL LOAD Ta : 25°C	I = 22 A/ 48VDC	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105 % ~ 135 %	I/P : 48VDC O/P : TESTING Ta : 25°C	122 %/ 48VDC Constant Current Limiting	P
2	OVER VOLTAGE PROTECTION	CH1 : 13.8 V ~ 16.2 V	I/P : 48VDC O/P : MIN LOAD Ta : 25°C	14.811 V/ 48VDC Shut down Re- power on to recover	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 67.2VDC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Constant Current Limiting recover automatically after fault condition is removed	P
4	OVER TEMPERATURE PROTECTION	SPEC : TSW1 : 90 ± 5°C O.T.P. NO DAMAGE	I/P : 48 VDC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage , recovers automatically after temperature goes down	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 2 Rated : SM2A01NFP 65A/200V	I/P : High-Line +3V =70.2V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 128 V (2) 99 V (3) 104 V	P
2	Diode Peak Voltage	Q101 Rated : IRFB3607PBF 80A/75V Q105 Rated : IRFB3607PBF 80A/75V	I/P : High-Line +3V = 70.2V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 68.8 V (2) 34 V (3) 36.8 V (1) 75 V (2) 74 V (3) 74 V	P
3	Input Capacitor Voltage	C5 Rated : 390u/100V UL10Kh ZLH	I/P : High-Line +3V = 70.2V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 70.16 V (2) 71.41 V (3) 71.41 V	P
4	Control IC Voltage Test	U 1 Rated : PWM LM5026MT 7.3V~16V	I/P : High-Line +3V = 70.2V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 15.612 V (2) 13.120 V (3) 15.612 V	P
5	Input Power Transistor (D to S) or (C to E) Peak Voltage	Q7 Rated : IRFB3607PBF 80A/75V	I/P : High-Line +3V = 70.2V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 50 V (2) 308 mV (3) 324 mV	P

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 4 KVDC/min I/P-FG : 2.5 KVDC/min O/P-FG : 2.5 KVDC/min	I/P-O/P : 4.4 KVDC/min I/P-FG : 3 KVDC/min O/P-FG : 3 KVDC/min Ta : 25°C	I/P-O/P : 0.002 mA I/P-FG : 0.002 mA O/P-FG : 0.002 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C /70%RH	I/P-O/P : 24.5 GΩ I/P-FG : 30 GΩ O/P-FG : 27.5 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	11 mΩ	P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RADIATION	EN55022 CLASS B	I/P : 48VDC O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
2	CONDUCTION	EN55022 CLASS A	I/P:48 VDC O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	P
3	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 48VDC O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
4	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT : 0.5KV	I/P : 48VDC O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	SURGE	IEC61000-4-5 MEDICAL LIGHT INDUSTRY L-N : 0.5KV L,N-PE : 0.5KV	I/P : 48VDC O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	Test by certified Lab & Test Report Prepare				

RELIABILITY TEST
ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																															
1	TEMPERATURE RISE TEST	MODEL : RSD-200B-12 1. ROOM AMBIENT BURN-IN : 13 HRS I/P : 24VDC O/P : FULL LOAD Ta= 24.8 °C 2. HIGH AMBIENT BURN-IN : 14 HRS I/P : 24VDC O/P : FULL LOAD Ta= 65.4 °C			P																																																																																															
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 24.8 °C</th> <th>HIGH AMBIENT Ta= 65.4 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>TR997</td><td>61.0°C</td><td>96.9°C</td></tr> <tr><td>2</td><td>Q7</td><td>AP9963GP 160A/40V TO220</td><td>62.8°C</td><td>97.6°C</td></tr> <tr><td>3</td><td>C12</td><td>470u/50V UL10Kh 12.5*20 YXG-LLC</td><td>62.3°C</td><td>97.6°C</td></tr> <tr><td>4</td><td>T2</td><td>TF2354</td><td>71.9°C</td><td>106.6°C</td></tr> <tr><td>5</td><td>C8</td><td>330u/50V UL10Kh 10*23 ZLH</td><td>65.5°C</td><td>100.3°C</td></tr> <tr><td>6</td><td>C60</td><td>47u/50V L5Kh 6.3*11 YXF</td><td>65.5°C</td><td>99.8°C</td></tr> <tr><td>7</td><td>C45</td><td>47u/63V UL7Kh 8*11.5 YXF</td><td>67.8°C</td><td>102.0°C</td></tr> <tr><td>8</td><td>C201</td><td>10u/50V UL10Kh 5*11 YXM</td><td>65.7°C</td><td>99.6°C</td></tr> <tr><td>9</td><td>Q1</td><td>IRFB3607PBF 80A/75V TO220</td><td>68.8°C</td><td>103.7°C</td></tr> <tr><td>10</td><td>Q3</td><td>IRFB3607PBF 80A/75V TO220</td><td>68.6°C</td><td>103.0°C</td></tr> <tr><td>11</td><td>TSW</td><td>115°C</td><td>68.8°C</td><td>102.0°C</td></tr> <tr><td>12</td><td>T1</td><td>TF2247</td><td>73.4°C</td><td>107.1°C</td></tr> <tr><td>13</td><td>C5</td><td>1000u/50V UL10Kh 16*25 ZLJ</td><td>65.4°C</td><td>100.5°C</td></tr> <tr><td>14</td><td>Q106</td><td>IRFB3607PBF 80A/75V TO220</td><td>59.1°C</td><td>92.7°C</td></tr> <tr><td>15</td><td>Q101</td><td>IRFB3607PBF 80A/75V TO220</td><td>68.5°C</td><td>103.0°C</td></tr> <tr><td>16</td><td>C105</td><td>1800u/16V UL10Kh 10*23 ZLH</td><td>67.3°C</td><td>102.0°C</td></tr> <tr><td>17</td><td>C108</td><td>1800u/16V UL10Kh 10*23 ZLH</td><td>68.0°C</td><td>102.4°C</td></tr> <tr><td>18</td><td>U1</td><td>LM5026MT TSSOP-16</td><td>66.2°C</td><td>100.7°C</td></tr> </tbody> </table>	NO	Position		P/N	ROOM AMBIENT Ta= 24.8 °C	HIGH AMBIENT Ta= 65.4 °C	1	LF1	TR997	61.0°C	96.9°C	2	Q7	AP9963GP 160A/40V TO220	62.8°C	97.6°C	3	C12	470u/50V UL10Kh 12.5*20 YXG-LLC	62.3°C	97.6°C	4	T2	TF2354	71.9°C	106.6°C	5	C8	330u/50V UL10Kh 10*23 ZLH	65.5°C	100.3°C	6	C60	47u/50V L5Kh 6.3*11 YXF	65.5°C	99.8°C	7	C45	47u/63V UL7Kh 8*11.5 YXF	67.8°C	102.0°C	8	C201	10u/50V UL10Kh 5*11 YXM	65.7°C	99.6°C	9	Q1	IRFB3607PBF 80A/75V TO220	68.8°C	103.7°C	10	Q3	IRFB3607PBF 80A/75V TO220	68.6°C	103.0°C	11	TSW	115°C	68.8°C	102.0°C	12	T1	TF2247	73.4°C	107.1°C	13	C5	1000u/50V UL10Kh 16*25 ZLJ	65.4°C	100.5°C	14	Q106	IRFB3607PBF 80A/75V TO220	59.1°C	92.7°C	15	Q101	IRFB3607PBF 80A/75V TO220	68.5°C	103.0°C	16	C105	1800u/16V UL10Kh 10*23 ZLH	67.3°C	102.0°C	17	C108	1800u/16V UL10Kh 10*23 ZLH	68.0°C	102.4°C	18	U1	LM5026MT TSSOP-16	66.2°C	100.7°C		
NO	Position	P/N	ROOM AMBIENT Ta= 24.8 °C	HIGH AMBIENT Ta= 65.4 °C																																																																																																
1	LF1	TR997	61.0°C	96.9°C																																																																																																
2	Q7	AP9963GP 160A/40V TO220	62.8°C	97.6°C																																																																																																
3	C12	470u/50V UL10Kh 12.5*20 YXG-LLC	62.3°C	97.6°C																																																																																																
4	T2	TF2354	71.9°C	106.6°C																																																																																																
5	C8	330u/50V UL10Kh 10*23 ZLH	65.5°C	100.3°C																																																																																																
6	C60	47u/50V L5Kh 6.3*11 YXF	65.5°C	99.8°C																																																																																																
7	C45	47u/63V UL7Kh 8*11.5 YXF	67.8°C	102.0°C																																																																																																
8	C201	10u/50V UL10Kh 5*11 YXM	65.7°C	99.6°C																																																																																																
9	Q1	IRFB3607PBF 80A/75V TO220	68.8°C	103.7°C																																																																																																
10	Q3	IRFB3607PBF 80A/75V TO220	68.6°C	103.0°C																																																																																																
11	TSW	115°C	68.8°C	102.0°C																																																																																																
12	T1	TF2247	73.4°C	107.1°C																																																																																																
13	C5	1000u/50V UL10Kh 16*25 ZLJ	65.4°C	100.5°C																																																																																																
14	Q106	IRFB3607PBF 80A/75V TO220	59.1°C	92.7°C																																																																																																
15	Q101	IRFB3607PBF 80A/75V TO220	68.5°C	103.0°C																																																																																																
16	C105	1800u/16V UL10Kh 10*23 ZLH	67.3°C	102.0°C																																																																																																
17	C108	1800u/16V UL10Kh 10*23 ZLH	68.0°C	102.4°C																																																																																																
18	U1	LM5026MT TSSOP-16	66.2°C	100.7°C																																																																																																
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 24VDC O/P : 121 % LOAD Ta : 25°C	TEST : OK	P																																																																																															
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 33.6VDC/14.4VDC O/P : 100 % LOAD Ta= -43 °C	TEST : OK	P																																																																																															
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 55 °C NO DAMAGE	I/P : 33.6 VDC O/P : FULL LOAD Ta= 55°C HUMIDITY= 95 %R.H	TEST : OK	P																																																																																															
5	TEMPERATURE COEFFICIENT	± 0.03 % (0~50°C)	I/P : 24VDC O/P : FULL LOAD	± 0.01 % (0~50°C)	P																																																																																															
6	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																																																															

7	THERMAL SHOCK TEST	1. Thermal shock Temperature : -45°C~ +60°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 48VDC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec	OK	P
8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 5G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK	P
9	CAPACITOR LIFE CYCLE	RSD-200B-12:SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 24VDC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 24VDC O/P : FULL LOAD Ta= 55 °C LIFE TIME (3) I/P : 24VDC O/P : 75% LOAD Ta= 55 °C LIFE TIME (4) I/P : 24VDC O/P : 50% LOAD Ta= 55 °C LIFE TIME	(1) 164897 HRS (2) 31018 HRS (3) 70372 HRS (4) 105804 HRS	P
10	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE : 218.2K HRS		P
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure(Expected Life) : 30,000 hours @ TA 55°C		P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2011/11/9	RD SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2012/1/5	PRODUCT SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2012/2/22	PRODUCT SAMPLE W1202B15	PASS	SANFORD SU	VINCENT TSENG

2009/08/04 A50-F023