



MODEL : SD-1000H-12

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 150 mVp-p (Max)	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	V1: 52 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1:11 V - 15 V	I/P: 96 VDC O/P:MIN LOAD Ta:25°C	10.32 V-15.67 V	P
3	OUTPUT VOLTAGE TOLERANCE	V1: 1%- -1 % (Max)	I/P: 96 VDC / 144VDC O/P:FULL/ MIN LOAD Ta:25°C	V1: 0.1 %~- -0.1 %	P
4	LINE REGULATION	V1: 0.5 %- -0.5 % (Max)	I/P: 96VDC ~ 144VDC O/P:FULL LOAD Ta:25°C	V1: 0.05 %~- -0.05 %	P
5	LOAD REGULATION	V1: 0.5 %- -0.5 % (Max)	I/P: 96 VDC O/P:FULL ~MIN LOAD Ta:25°C	V1: 0.1 %~- -0.1 %	P
6	SET UP TIME	500 ms (Max)	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	135 ms	P
7	RISE TIME	50 ms (Max)	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	32 ms	P
8	OVER/UNDERSHOOT TEST	< ±5%	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	TEST: < 5 %	P
9	DYNAMIC LOAD	V1: 1200 mVp-p	I/P: 96 VDC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	738 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	72VDC~ 144VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	70.1V~ 144V	P
			I/P: LOW-LINE-0.2V= 71.8V HIGH-LINE+5%= 151V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	EFFICIENCY	85 % (TYP)	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	86.6 %	P
3	INPUT CURRENT	11.6 A / 96 V(TYP)	I/P: 96VDC O/P:FULL LOAD Ta:25°C	I = 8.76 A	P
4	INRUSH CURRENT	100 A /96V (TYP) COLD START	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	I = 79 A	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105 %- 125 %	I/P: 96VDC O/P:TESTING Ta:25°C	118 % Constant Current Limiting, unit will shut down o/p voltage above 5sec Re-power on to recover	P
2	OVER VOLTAGE PROTECTION	CH1: 16V~ 19V	I/P: 96VDC O/P:MIN LOAD Ta:25°C	17.4 V Shunt down Re- power ON	P
3	OVER TEMPERATURE PROTECTION	SPEC: 75°C ±5°C OT.P. (TSW1) 85°C ±5°C OT.P. (TSW2) NO DAMAGE	I/P: 96 VDC O/P:FULL LOAD	O.T.P. Active Shut down o/p volotage , recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 144VDC O/P: FULL LOAD Ta:25°C	NO DAMAGE Constant Current Limiting, unit will shut down o/p voltage above 5sec Re-power on to recover	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	FAN SPEED CONTROL	0%LOAD=6V-8.5V 100%LOAD=11.8V-12.8V	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	Fan Voltage= 7.57 V/ NO LOAD Fan Voltage= 12.38 V/ 100%LOAD	P
2	REMOTE CONTROL	Rc+ / Rc- POWER ON:OPEN BETWEEN ON/OFF POWEROFF:SHORT BETWEEN ON/OFF (A) Using External Voltage Source (B) Using Internal 12V Auxiliary Output (C) Using Internal 12V Auxiliary Output (D)	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	(A)OK (B)OK (C)OK	P
3	REMOTE SENSE	>0.3V	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	> 0.3V	P
4	OUTPUT OK SIGNAL	OPEN COLLECTOR SIGNAL LOW WHEN PSU TURN ON,MAX.SINK CURRENT 10mA,external voltage is 13V 0-0.5V OUTPUT STATUS ON 12-13V OUTPUT STATUS OFF	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	SINK CURRENT: 10 mA OUTPUT STATUS ON= 0 V OUTPUT STATUS OFF=12.59V	P
5	FAN LOCK	SHUTDOWN RE-POWER ON	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	SHUTDOWN RE-POWER ON	P
6	AUX POWER	0-0.25A(10.8V-13.2V)	I/P: 96VDC Ta:25°C	13.12 V/0A 12.25 V/0.25A	P
7	DC I/P UVP	69V-71.6V	O/P:100% LOAD Ta:25°C	70.1VDC	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																																																			
1	TEMPERATURE RISE TEST	MODEL : SD-1000H-24 1. ROOM AMBIENT BURN-IN : 1 HRS I/P: 96VDC O/P: FULL LOAD Ta= 28.1°C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P: 96VDC O/P: FULL LOAD Ta= 53.7°C			P																																																																																																																			
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 28.1 °C</th> <th>HIGH AMBIENT Ta= 53.7 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>U2</td><td>UCC28220D</td><td>41.4°C</td><td>63.2°C</td></tr> <tr><td>2</td><td>D2</td><td>S20LC20U 20A/200V</td><td>37.0°C</td><td>58.3°C</td></tr> <tr><td>3</td><td>Q3</td><td>IRFP260N 50A/200V</td><td>42.8°C</td><td>64.2°C</td></tr> <tr><td>4</td><td>Q1</td><td>IRFP260N 50A/200V</td><td>42.3°C</td><td>63.5°C</td></tr> <tr><td>5</td><td>TSW1</td><td>ST-22 75°C</td><td>38.2°C</td><td>59.1°C</td></tr> <tr><td>6</td><td>LF1</td><td>TR-776</td><td>43.6°C</td><td>65.3°C</td></tr> <tr><td>7</td><td>C8</td><td>470U/200V 105°C MXR</td><td>39.4°C</td><td>59.9°C</td></tr> <tr><td>8</td><td>T2 COIL</td><td>TF-1688A</td><td>57.2°C</td><td>80.4°C</td></tr> <tr><td>9</td><td>D901</td><td>S3L60 2.2A/600V</td><td>47.1°C</td><td>69.1°C</td></tr> <tr><td>10</td><td>L2</td><td>TF-1680</td><td>52.4°C</td><td>74.4°C</td></tr> <tr><td>11</td><td>U9</td><td>TNY280PN</td><td>47.0°C</td><td>69.7°C</td></tr> <tr><td>12</td><td>ZD10</td><td>P6KE100A</td><td>47.8°C</td><td>70.3°C</td></tr> <tr><td>13</td><td>U1</td><td>IR1150IS(PbF)</td><td>37.1°C</td><td>57.7°C</td></tr> <tr><td>14</td><td>Q903</td><td>IRFP460A 20A/500V</td><td>55.3°C</td><td>79.9°C</td></tr> <tr><td>15</td><td>C303</td><td>100U/25V 105°C YXG</td><td>46.5°C</td><td>68.9°C</td></tr> <tr><td>16</td><td>L100</td><td>TF-1455</td><td>50.9°C</td><td>73.7°C</td></tr> <tr><td>17</td><td>Q161</td><td>TIP42C -5A/100V</td><td>46.1°C</td><td>68.1°C</td></tr> <tr><td>18</td><td>TSW2</td><td>ST-22 85°C</td><td>57.9°C</td><td>80.4°C</td></tr> <tr><td>19</td><td>D202</td><td>ESAD83-006 30A/60V</td><td>63.7°C</td><td>86.3°C</td></tr> <tr><td>20</td><td>PCB</td><td>T2 與 ZD10 間</td><td>50.5°C</td><td>73.6°C</td></tr> <tr><td>21</td><td>內 TA</td><td>C303 上方處</td><td>43.2°C</td><td>65.3°C</td></tr> <tr><td>22</td><td>C113</td><td>1000U/35V 105°C YXG</td><td>51.0°C</td><td>73.5°C</td></tr> </tbody> </table>	NO	Position		P/N	ROOM AMBIENT Ta= 28.1 °C	HIGH AMBIENT Ta= 53.7 °C	1	U2	UCC28220D	41.4°C	63.2°C	2	D2	S20LC20U 20A/200V	37.0°C	58.3°C	3	Q3	IRFP260N 50A/200V	42.8°C	64.2°C	4	Q1	IRFP260N 50A/200V	42.3°C	63.5°C	5	TSW1	ST-22 75°C	38.2°C	59.1°C	6	LF1	TR-776	43.6°C	65.3°C	7	C8	470U/200V 105°C MXR	39.4°C	59.9°C	8	T2 COIL	TF-1688A	57.2°C	80.4°C	9	D901	S3L60 2.2A/600V	47.1°C	69.1°C	10	L2	TF-1680	52.4°C	74.4°C	11	U9	TNY280PN	47.0°C	69.7°C	12	ZD10	P6KE100A	47.8°C	70.3°C	13	U1	IR1150IS(PbF)	37.1°C	57.7°C	14	Q903	IRFP460A 20A/500V	55.3°C	79.9°C	15	C303	100U/25V 105°C YXG	46.5°C	68.9°C	16	L100	TF-1455	50.9°C	73.7°C	17	Q161	TIP42C -5A/100V	46.1°C	68.1°C	18	TSW2	ST-22 85°C	57.9°C	80.4°C	19	D202	ESAD83-006 30A/60V	63.7°C	86.3°C	20	PCB	T2 與 ZD10 間	50.5°C	73.6°C	21	內 TA	C303 上方處	43.2°C	65.3°C	22	C113	1000U/35V 105°C YXG	51.0°C	73.5°C		
NO	Position	P/N	ROOM AMBIENT Ta= 28.1 °C	HIGH AMBIENT Ta= 53.7 °C																																																																																																																				
1	U2	UCC28220D	41.4°C	63.2°C																																																																																																																				
2	D2	S20LC20U 20A/200V	37.0°C	58.3°C																																																																																																																				
3	Q3	IRFP260N 50A/200V	42.8°C	64.2°C																																																																																																																				
4	Q1	IRFP260N 50A/200V	42.3°C	63.5°C																																																																																																																				
5	TSW1	ST-22 75°C	38.2°C	59.1°C																																																																																																																				
6	LF1	TR-776	43.6°C	65.3°C																																																																																																																				
7	C8	470U/200V 105°C MXR	39.4°C	59.9°C																																																																																																																				
8	T2 COIL	TF-1688A	57.2°C	80.4°C																																																																																																																				
9	D901	S3L60 2.2A/600V	47.1°C	69.1°C																																																																																																																				
10	L2	TF-1680	52.4°C	74.4°C																																																																																																																				
11	U9	TNY280PN	47.0°C	69.7°C																																																																																																																				
12	ZD10	P6KE100A	47.8°C	70.3°C																																																																																																																				
13	U1	IR1150IS(PbF)	37.1°C	57.7°C																																																																																																																				
14	Q903	IRFP460A 20A/500V	55.3°C	79.9°C																																																																																																																				
15	C303	100U/25V 105°C YXG	46.5°C	68.9°C																																																																																																																				
16	L100	TF-1455	50.9°C	73.7°C																																																																																																																				
17	Q161	TIP42C -5A/100V	46.1°C	68.1°C																																																																																																																				
18	TSW2	ST-22 85°C	57.9°C	80.4°C																																																																																																																				
19	D202	ESAD83-006 30A/60V	63.7°C	86.3°C																																																																																																																				
20	PCB	T2 與 ZD10 間	50.5°C	73.6°C																																																																																																																				
21	內 TA	C303 上方處	43.2°C	65.3°C																																																																																																																				
22	C113	1000U/35V 105°C YXG	51.0°C	73.5°C																																																																																																																				
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 96VDC O/P: 112% LOAD Ta:25°C	TEST : OK	P																																																																																																																			
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 96VDC O/P: 100% LOAD Ta= -20 °C	TEST : OK	P																																																																																																																			
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50°C NO DAMAGE	I/P: 147 VDC O/P:FULL LOAD Ta= 50°C HUMIDITY= 95 %R.H	TEST : OK	P																																																																																																																			
5	TEMPERATURE COEFFICIENT	± 0.02%(0-50°C)	I/P: 96 VDC O/P:FULL LOAD	± 0.0017 %(0-50°C)	P																																																																																																																			
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10~500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	P																																																																																																																			

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 2 KVAC/min I/P-FG: 1.5 KVAC/min O/P-FG: 0.5 KVAC/min	I/P-O/P: 2.4 KVAC/min I/P-FG: 1.8 KVAC/min O/P-FG: 0.6 KVAC/min Ta:25°C / 70%RH	I/P-O/P: 4.67 mA I/P-FG: 4.46 mA O/P-FG: 4.11 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 5 GΩ I/P-FG: 2 GΩ O/P-FG: 14 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta:25°C / 70%RH	8mΩ	P
4	APPROVAL	TUV: Certificate NO : UL: File NO :			N/A

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RADIATION	EN55022 CLASS B	I/P: 96VDC O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	P
2	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	CRITERIA A	P
3	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 96VDC O/P:FULL LOAD Ta:25°C	CRITERIA A	P
4	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N :0.5KV L,N-PE:0.5KV	I/P: 96 VDC O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SD-1000H-24 : SUPPOSE C113 IS THE MOST CRITICAL COMPONENT I/P: 96VDC O/P:FULL LOAD Ta=25 °C LIFE TIME= 370952 HRS I/P: 96VDC O/P:FULL LOAD Ta=50 °C LIFE TIME= 91276 HRS			P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 32KHRS			P
3	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure : Above 30,000 hours @ TA 50°C			P



COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 900 Rated IRFP460A 20A/500V	I/P:High-Line +3V = 147V O/P: (1)Full Load Turn on (2) Output Short Ta:25°C	(1) 370 V (2) 348 V	P
2	Diode Peak Voltage	D101 Rated ESAD83-006 30A/60V	I/P:High-Line +3V = 147 V O/P: (1)Full Load Turn on (2)Output Short Ta:25°C	(1) 41 V (2) 22 VV	P
3	Clamp Diode Peak Voltage	D 900 Rated S3L60 2.2A/600V	I/P:High-Line +3V = 147 V O/P: (1) Dynamic Load 90%Duty/1KHz Ta:25°C	(1) 342 V	P
4	Input Capacitor Voltage	C5 Rated 470u/200V 105°C	I/P:High-Line +3V = 147 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 151 V (2) 151 V (3) 151 V	P
5	Control IC Voltage Test	U2 Rated UCC28220: 8V-14 V	I/P:High-Line +3V = 147 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 13.68 V (2) 13.45 V (3) 13.68 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2007/9/14	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2007/11/16	PRODUCT SAMPLE W0710C50	PASS	VINCENT TSENG	MAX LIN
2008/1/10	PRODUCT SAMPLE W0712C58	PASS	SANFORD SU	VINCENT TSENG

2003/12/12 A50-F023