



Test Report : SKA60C-05

60W DC-DC Regulated Single Output Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-2%~+2% (Max)	I/P:48VDC O/P:FULL LOAD Ta:25°C	0.36 %	P
2	RIPPLE & NOISE	60mVp-p (Max)	I/P:48VDC O/P:FULL LOAD Ta:25°C	26 mV	P
3	LINE REGULATION	-0.5%~+0.5% (Max)	I/P:36VDC~75VDC O/P:FULL LOAD Ta:25°C	-0 % ~ +0 %	P
4	LOAD REGULATION	-0.5%~+0.5% (Max)	I/P:48VDC O/P:MIN-FULL LOAD Ta:25°C	-0.12 % ~ +0.1 %	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	36 VDC ~ 75 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	31 VDC ~ 75 VDC	P
2	EFFICIENCY	92% (Typ)	I/P:48VDC O/P:FULL LOAD Ta:25°C	92.17 %	P
3	DC CURRENT	1370 mA / FULL LOAD (Max) 60 mA / NO LOAD (Max)	I/P:48VDC O/P:NO / FULL LOAD Ta:25°C	1361 mA / FULL LOAD 46 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110%~160%	I/P:48VDC O/P:TESTING Ta:25°C	136 % HICCUP MODE AUTO-RECOVER	P
2	INPUT OVER VOLTAGE PROTECTION	80 VDC ~ 100 VDC	I/P:TESTING O/P:MIN LOAD Ta:25°C	81.3 VDC SHUTDOWN AUTO-RECOVER	P
3	OUTPUT OVER VOLTAGE PROTECTION	7 VDC ~ 8.95 VDC	I/P:48VDC O/P:MIN LOAD Ta:25°C	CLAMP BY TVS DIODE	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:75VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE AUTO-RECOVER	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Power on : R.C >2.5Vdc or open Power off : R.C <0.5Vdc or short (-Vin)	I/P:48VDC O/P:FULL LOAD Ta:25°C	Power on : R.C>1.2Vdc or Open Power off : R.C<1.0Vdc or Short	P
2	REMOTE SENSE	YES	I/P:48VDC O/P:FULL LOAD Ta:25°C	OK	P
3	TRIM	-10%~ +10% (Typ) Trim ~ +Vout Trim DOWN Trim ~ -Vout Trim UP Using 1M ohms VR	I/P:48VDC O/P:FULL LOAD Ta:25°C	Trim DOWN -10.1% Trim UP +13.4%	P

SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT										
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:24VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 24HRS I/P:24VDC O/P:FULL LOAD Ta=55°C			P										
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>CENTER</td> <td>70.8°C</td> <td>108.4°C</td> </tr> </tbody> </table>				NO	Position	P/N	1	2	1	CASE	CENTER	70.8°C	108.4°C
NO	Position	P/N	1	2											
1	CASE	CENTER	70.8°C	108.4°C											
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:24VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P										

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2012.4.6	RD SAMPLE	PASS	PETER	VINCENT