

## 0.5W DC-DC Regulated Single Output



- 1000VDC I/O isolation
- Internal SMD technology
- Built-in EMI filter
- Protection: Short circuit
- Cooling by free air convection
- Non-conductive plastic case
- Dual in line package
- 100% full load burn-in test
- Low cost, high reliability
- 2 years warranty

Mechanism		Pin Configuration											
<p>Unit: mm(inch)</p>		<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Pin No.</th><th>Output</th></tr> </thead> <tbody> <tr> <td>1 &amp; 16</td><td>+Vin</td></tr> <tr> <td>6 &amp; 11</td><td>-Vout</td></tr> <tr> <td>7 &amp; 10</td><td>+Vout</td></tr> <tr> <td>8 &amp; 9</td><td>-Vin</td></tr> </tbody> </table>		Pin No.	Output	1 & 16	+Vin	6 & 11	-Vout	7 & 10	+Vout	8 & 9	-Vin
Pin No.	Output												
1 & 16	+Vin												
6 & 11	-Vout												
7 & 10	+Vout												
8 & 9	-Vin												

Voltage set point accuracy....±2% (typical)  
 Line regulation .....±1% (max.)  
 Load regulation .....±1% (max.)@10~100% load  
 Input reflected ripple .....120mVp-p  
 Efficiency .....60% (typical)  
 Short circuit protection .....continuous, auto-recovery  
 Switching frequency .....50kHz (min.)  
 I/O isolation voltage .....1000VDC (min.)  
 I/O isolation resistance .....100MΩ (min.)@ 500VDC  
 Isolation capacitance .....80pF (max.)  
 Working temperature .....-25°C to +60°C (no derating), +71°C@80% load  
 Storage temperature .....-25°C to +105°C  
 Temp. Coefficient .....±0.03% / °C (max.)  
 Case material .....non-conductive plastic

Model No.	Input (VDC)	Output (VDC)	Current (mA)	R&N (mVp-p)
SRS-0505	5±10%	5	100	100
SRS-0509	5±10%	9	56	100
SRS-0512	5±10%	12	42	100
SRS-0515	5±10%	15	34	100
SRS-1205	12±10%	5	100	100
SRS-1209	12±10%	9	56	100
SRS-1212	12±10%	12	42	100
SRS-1215	12±10%	15	34	100
SRS-2405	24±10%	5	100	100
SRS-2409	24±10%	9	56	100
SRS-2412	24±10%	12	42	100
SRS-2415	24±10%	15	34	100
SRS-4805	48±10%	5	100	100
SRS-4809	48±10%	9	56	100
SRS-4812	48±10%	12	42	100
SRS-4815	48±10%	15	34	100