

MODEL : USP-150-12

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1:150 mVp-p (Max)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	V1: 70 mVp-p (Max)	PASS
2	OUTPUT VOLTAGE ADJUST RANGE	CH1: 11.0 V~ 13.2 V	I/P: 230 VAC I/P:115VAC O/P:MIN LOAD Ta:25°C	10.770V~13.795V/230VAC 10.767V~13.795V/115VAC	PASS
3	OUTPUT VOLTAGE TOLERANCE	V1: -2 %~ +2 % (Max)	I/P: 90 VAC / 295 VAC O/P:FULL/ NO LOAD Ta:25°C	V1: -0.208 %~ 0.367 %	PASS
4	LINE REGULATION	V1: -0.5 %~ +0.5 % (Max)	I/P: 100 VAC ~ 295 VAC O/P:FULL LOAD Ta:25°C	V1: -0.008 %~ 0.008 %	PASS
5	LOAD REGULATION	V1: -1 %~ +1 % (Max)	I/P: 230 VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: -0.207 %~ 0.149 %	PASS
6	SET UP TIME	230VAC/ 2000 ms (Max) 115VAC/ 3000 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 832.446 ms 115 VAC/1658.056 ms	PASS
7	RISE TIME	230VAC/ 100 ms (Max) 115 VAC/ 100 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230 VAC/ 4.623 ms 115 VAC/ 4.726 ms	PASS
8	HOLD UP TIME	230VAC/ 16 ms (Typ) 115VAC/ 16 ms (Typ)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 21.360 ms 115VAC/ 21.421 ms	PASS
9	OVER/UNDERSHOOT TEST	< ± 5 %	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: +4.305 % -1.325 %	PASS
10	DYNAMIC LOAD	V1: 1200 mVp-p	I/P : 230 VAC (1)O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2)O/P : FULL /Min LOAD 90%DUTY/ 3KHZ (3)O/P : FULL /Min LOAD 90%DUTY/ 5KHZ (4)O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1) 360 mVp-p (2) 350 mVp-p (3) 350 mVp-p (4) 340 mVp-p	PASS
11	BURN-IN TEST	(1)HI-LINE (a)0%~100% (b)100%~0% (2)LOW-LINE (a)0%~100% (b)100%~0% (3)NORNAL-LINE (a)0%~100% (b)100%~0% (4)NO/FULL LOAD SWITCH	I/P:HI/LOW/NORNAL-LINE 63Hz/47Hz O/P:(1) (a)0%~100% (b)100%~0% (2) (a)0%~100% (b)100%~0% (3) (a)0%~100% (b)100%~0% (4) NO/FULL LOAD SWITCH Ta : 25°C	(1) a.OK b.OK (2) a.OK b.OK (3) a.OK b.OK (4)OK	PASS

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	90VAC~ 295VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	80 V~ 295 V	PASS
			(1)I/P: LOW-LINE-3V= 87 V HIGH-LINE+10V= 305 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (2) I/P:230VAC ON: 0.5 Sec . OFF: 0.5 Sec 20MIN (AC POWER ON/OFF NO DAMAGE)	TEST: (1)OK (2)OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P: 90VAC ~ 295 VAC O/P:FULL-MIN LOAD Ta:25°C	TEST: OK	PASS
3	POWER FACTOR	0.96/ 230 VAC(Typ) 0.98/ 115 VAC(Typ)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	PF= 0.978 / 230VAC PF= 0.997 / 115VAC	PASS
4	EFFICIENCY	91.5% (Typ)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	91.81 %	PASS
5	INPUT CURRENT	230 V/ 1 A (Typ) 115 V/ 2 A (Typ)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	I = 0.736 A/ 230VAC I = 1.475 A/ 115VAC	PASS
6	INRUSH CURRENT	230 V/ 65 A (Typ) COLD START	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	I = 48.921 A/ 230VAC	PASS
7	LEAKAGE CURRENT	< 2 mA / 240VAC EN 60950-1	I/P:295 VAC O/P:NO LOAD Ta:25°C	L-FG: 0.266 mA N-FG: 0.266 mA	PASS

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110%~ 160% RATED OUTPUT POWER	I/P: 100 VAC I/P: 230 VAC I/P: 295 VAC O/P:TESTING Ta:25°C	145.9 %/ 100 VAC 145.5 %/ 230VAC 145.3 %/ 295 VAC Hiccup Mode	PASS
2	OVER VOLTAGE PROTECTION	CH1: 13.6V~ 16.3V	I/P: 90 VAC I/P: 230 VAC I/P: 295 VAC O/P:MIN LOAD Ta:25°C	15.34 V/ 90 VAC 15.38 V/ 230VAC 15.40 V/ 295 VAC Shut down o/p voltage with auto-recovery or re-power on to recovery	PASS
3	OVER TEMPERATURE PROTECTION	SPEC: RTH2 100 °C ± 5 °C O.T.P. NO DAMAGE	I/P: 230 VAC O/P:FULL LOAD	96.9 °C / 230 VAC O.T.P. Active Shut down o/p voltage. recovers automatically after temperature goes down	PASS
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 295 VAC O/P: FULL LOAD Ta:25°C	NO DAMAGE Hiccup Mode	PASS

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-FG: 1.5 KVAC/min I/P-O/P: 3.0 KVAC/min O/P-FG: 0.5 KVAC/min EN 60950-1	I/P-FG: 1.8 KVAC/min I/P-O/P: 3.6 KVAC/min O/P-FG: 0.6 KVAC/min Ta:25°C	I/P-FG: 2.461 mA I/P-O/P: 3.197 mA O/P-FG: 3.787 mA NO DAMAGE	PASS
2	ISOLATION RESISTANCE	I/P-FG: 500VDC>100MΩ I/P-O/P:500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-FG: 500 VDC I/P-O/P: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-FG: >9999 MΩ I/P-O/P: >9999 MΩ O/P-FG: >9999 MΩ NO DAMAGE	PASS
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ EN 60950-1	40 A / 2 min Ta:25°C	9 mΩ	PASS

E.M.C TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 230 VAC/50HZ O/P:100% LOAD Ta:25°C	PASS	PASS
2	CONDUCTION	EN55022 CLASS B	I/P:230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	PASS
3	RADIATION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	PASS
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	PASS
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	PASS
6	SURGE	EN61000-4-5 INDUSTRY L-N :2KV L,N-PE:4KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	PASS
7	Test by certified Lab & Test Report Prepare				

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 230 VAC O/P: 145 % LOAD Ta:25°C	TEST : OK	PASS
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 295 VAC/100 VAC O/P: 100% LOAD Ta= -30°C	TEST : OK	PASS
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 55 °C NO DAMAGE	I/P: 298 VAC O/P:FULL LOAD Ta= 55 °C HUMIDITY= 95 %R.H	TEST : OK	PASS

4	TEMPERATURE COEFFICIENT	± 0.03 %(0~60℃)	I/P: 230 VAC O/P:FULL LOAD	± 0.002 %(0~60℃)	PASS																																																																																																									
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45℃~ +90℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		TEST : OK	PASS																																																																																																									
6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -30℃~ + 55℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load		TEST : OK	PASS																																																																																																									
7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10~500Hz (3) Sweep Time:12min/sweep cycle (4) Acceleration:2G (加严 3G TEST 及加测 RANDOM TEST) (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25℃		TEST : OK	PASS																																																																																																									
8	CAPACITOR LIFE CYCLE	SUPPOSE C 102 IS THE MOST CRITICAL COMPONENT (1) I/P: 230 VAC O/P:FULL LOAD Ta= 25 ℃ LIFE TIME= 707733 HRS (2) I/P: 230 VAC O/P:FULL LOAD Ta= 55 ℃ LIFE TIME= 83068 HRS			PASS																																																																																																									
9	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 216.3K HRS			PASS																																																																																																									
10	TEMPERATURE RISE TEST	MODEL : USP-150-12 1. ROOM AMBIENT BURN-IN : 2 HRS I/P: 230 VAC O/P: 100% LOAD Ta= 25.3 ℃ 2. HIGH AMBIENT BURN-IN : 2 HRS I/P: 230 VAC O/P: 100% LOAD Ta= 54.7 ℃			PASS																																																																																																									
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 25.3 ℃</th> <th>HIGH AMBIENT Ta= 54.7 ℃</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF2</td><td>TR-652</td><td>47.0℃</td><td>77.8℃</td></tr> <tr><td>2</td><td>BD1</td><td>GBU408</td><td>51.8℃</td><td>82.1℃</td></tr> <tr><td>3</td><td>RTH2</td><td>NTC 220K Ω</td><td>57.5℃</td><td>89.3℃</td></tr> <tr><td>4</td><td>L1</td><td>TR-654</td><td>51.1℃</td><td>79.2℃</td></tr> <tr><td>5</td><td>L2</td><td>TF-6294</td><td>57.2℃</td><td>87.1℃</td></tr> <tr><td>6</td><td>D2</td><td>8E2TH06FP</td><td>61.1℃</td><td>89.9℃</td></tr> <tr><td>7</td><td>Q5</td><td>STF13NM50N</td><td>56.5℃</td><td>85.9℃</td></tr> <tr><td>8</td><td>Q1</td><td>STF22NM60N</td><td>52.4℃</td><td>81.8℃</td></tr> <tr><td>9</td><td>T1</td><td>TF-6288</td><td>77.1℃</td><td>100.8℃</td></tr> <tr><td>10</td><td>Q101</td><td>IRF1405PBF</td><td>53.4℃</td><td>93.4℃</td></tr> <tr><td>11</td><td>U1</td><td>NCP1608B</td><td>54.0℃</td><td>89.1℃</td></tr> <tr><td>12</td><td>U900</td><td>L6599AD</td><td>56.8℃</td><td>84.8℃</td></tr> <tr><td>13</td><td>C33</td><td>223/1KV</td><td>54.5℃</td><td>84.6℃</td></tr> <tr><td>14</td><td>C5</td><td>100uF/450V KXG</td><td>53.7℃</td><td>82.1℃</td></tr> <tr><td>15</td><td>C38</td><td>100uF/25V YXM</td><td>54.3℃</td><td>84.4℃</td></tr> <tr><td>16</td><td>C16</td><td>100uF/50V KY</td><td>56.7℃</td><td>82.4℃</td></tr> <tr><td>17</td><td>C201</td><td>47uF/50V YXM</td><td>58.7℃</td><td>90.3℃</td></tr> <tr><td>18</td><td>C61</td><td>47uF/25V YXM</td><td>56.9℃</td><td>82.3℃</td></tr> <tr><td>19</td><td>C102</td><td>2200uF/16V ZLH</td><td>46.8℃</td><td>77.1℃</td></tr> <tr><td>20</td><td>C104</td><td>2200uF/16V ZLH</td><td>42.9℃</td><td>71.2℃</td></tr> </tbody> </table>				NO	Position	P/N	ROOM AMBIENT Ta= 25.3 ℃	HIGH AMBIENT Ta= 54.7 ℃	1	LF2	TR-652	47.0℃	77.8℃	2	BD1	GBU408	51.8℃	82.1℃	3	RTH2	NTC 220K Ω	57.5℃	89.3℃	4	L1	TR-654	51.1℃	79.2℃	5	L2	TF-6294	57.2℃	87.1℃	6	D2	8E2TH06FP	61.1℃	89.9℃	7	Q5	STF13NM50N	56.5℃	85.9℃	8	Q1	STF22NM60N	52.4℃	81.8℃	9	T1	TF-6288	77.1℃	100.8℃	10	Q101	IRF1405PBF	53.4℃	93.4℃	11	U1	NCP1608B	54.0℃	89.1℃	12	U900	L6599AD	56.8℃	84.8℃	13	C33	223/1KV	54.5℃	84.6℃	14	C5	100uF/450V KXG	53.7℃	82.1℃	15	C38	100uF/25V YXM	54.3℃	84.4℃	16	C16	100uF/50V KY	56.7℃	82.4℃	17	C201	47uF/50V YXM	58.7℃	90.3℃	18	C61	47uF/25V YXM	56.9℃	82.3℃	19	C102	2200uF/16V ZLH	46.8℃	77.1℃	20	C104	2200uF/16V ZLH	42.9℃	71.2℃
NO	Position	P/N	ROOM AMBIENT Ta= 25.3 ℃	HIGH AMBIENT Ta= 54.7 ℃																																																																																																										
1	LF2	TR-652	47.0℃	77.8℃																																																																																																										
2	BD1	GBU408	51.8℃	82.1℃																																																																																																										
3	RTH2	NTC 220K Ω	57.5℃	89.3℃																																																																																																										
4	L1	TR-654	51.1℃	79.2℃																																																																																																										
5	L2	TF-6294	57.2℃	87.1℃																																																																																																										
6	D2	8E2TH06FP	61.1℃	89.9℃																																																																																																										
7	Q5	STF13NM50N	56.5℃	85.9℃																																																																																																										
8	Q1	STF22NM60N	52.4℃	81.8℃																																																																																																										
9	T1	TF-6288	77.1℃	100.8℃																																																																																																										
10	Q101	IRF1405PBF	53.4℃	93.4℃																																																																																																										
11	U1	NCP1608B	54.0℃	89.1℃																																																																																																										
12	U900	L6599AD	56.8℃	84.8℃																																																																																																										
13	C33	223/1KV	54.5℃	84.6℃																																																																																																										
14	C5	100uF/450V KXG	53.7℃	82.1℃																																																																																																										
15	C38	100uF/25V YXM	54.3℃	84.4℃																																																																																																										
16	C16	100uF/50V KY	56.7℃	82.4℃																																																																																																										
17	C201	47uF/50V YXM	58.7℃	90.3℃																																																																																																										
18	C61	47uF/25V YXM	56.9℃	82.3℃																																																																																																										
19	C102	2200uF/16V ZLH	46.8℃	77.1℃																																																																																																										
20	C104	2200uF/16V ZLH	42.9℃	71.2℃																																																																																																										

COMPONENT STRESS TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q5 Rated STF13NM50N : 500 V 12 A	I/P:High-Line +3V = 298 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz I/P:Low-Line -3V = 87 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz Ta:25°C	(1) 468 V (2) 464 V (3) 454 V (4) 452 V (1) 468 V (2) 440 V (3) 454 V (4) 452 V	PASS
2	Diode Peak Voltage	Q101 Rated IRF1405PBF: 75 V 80 A	I/P:High-Line +3V =298 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz I/P:Low-Line -3V =87 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz Ta:25°C	(1) 44.6 V (2) 22.1 V (3) 42.2 V (4) 42.2 V (1) 55.4 V (2) 16.5 V (3) 44.2 V (4) 42.0 V	PASS
3	Input Capacitor Voltage	C 5 Rated NCC : 100u / 450 V 105°C / KXG Series	I/P:High-Line +3V = 298 V O/P: (1)Full Load input on/off (2) Min load input on /Off (3)Burn-IN 1 Hour Ta:25°C	(1) 470 V (2) 470 V (3) 441 V	PASS
4	Control IC Voltage Test	U 1 Rated NCP1608B: 20 V U 900 Rated L6599AD: 16 V	I/P:High-Line +3V =298 V O/P:(1).FULL LOAD (2). Output Short (3).O.L.P (4).O.V.P (5).NO LOAD VR 下限.LOW LINE Ta:25°C	U1 U900 (1) 17.1 V (1) 12.9 V (2) 18.4 V (2) 12.9 V (3) 18.4 V (3) 12.8 V (4) 18.4 V (4) 12.8 V (5) 16.9 V (5) 12.9 V	PASS



5	P.F.C Transistor (D to S) or (C to E) Peak Voltage	Q 1 Rated STF22NM60N: 600 V 16 A	<p>I/P:High-Line +3V = 298 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz</p> <p>I/P:Low-Line -3V = 87 V O/P: (1)Full Load input on/off (2)Output Short (3)Dynamic Load Full Load/ Min. Load 90%Duty/3KHz (4)Dynamic Load 50% Load/ Min. Load 50%Duty/120Hz</p> <p>Ta:25°C</p>	<p>(1) 490V (2) 464V (3) 456V (4) 456V</p> <p>(1) 500V (2) 474V (3) 470V (4) 454V</p>	PASS
---	--	-------------------------------------	--	---	------

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2010/3/20	RD SAMPLE	PASS	SKY	HOWAY
2011/1/20	PRODUCT SAMPLE	PASS	SKY	HOWAY